


# NIBCO®

AHEAD OF THE FLOW®



Copper Fittings

# Business-to-Business Solutions

Look to NIBCO for technology leadership.

The velocity with which e-business evolves demands that new products and services be continuously developed and introduced to keep our customers at the center of our business efforts. NIBCO provides an entire suite of business-to-business solutions that is changing the way we interact with customers.



[NIBCOpartner.com<sup>SM</sup>](#) is an exclusive set of secure web applications that allow quick access to customer-specific information and online order processing. This self-service approach gives you 24/7 access to your order status putting you in total control of your business.

Real time information includes:

- Online order entry
- Viewable invoices & reports
- Inventory availability
- Current price checks
- Order status
- Online library of price sheets, catalogs & submittals



**Electronic Data Interchange (EDI)** makes it possible to trade business documents at the speed of light. This technology cuts the cost of each transaction by eliminating the manual labor and paperwork involved in traditional order taking. This amounts to cost-savings, increased accuracy and better use of resources.

With EDI, you can trade:

- Purchase orders
- PO Acknowledgements
- Invoices
- Product activity data
- Advanced ship notices
- Remittance advice



**Vendor Managed Inventory (VMI)**, a sophisticated service for automated inventory management, reduces your overhead by transferring inventory management, order entry and forecasting to NIBCO. This is an on-going, interactive partnership with NIBCO.

Through automation, VMI brings results:

- Improves customer service
- Optimum inventory efficiencies
- Better forecasting
- Cuts transaction costs
- Peace of mind
- Relief from day-to-day management



## Table of Contents

Specifications .....	4
Wrot & Cast Pressure Fittings .....	5-21
Cast Copper Alloy Flared Fittings .....	22-24
Copper Insert Fittings for Polybutylene .....	25-26
Wrot & Cast DWV Fittings .....	27-37
Engineering Data .....	38-47
Installation Instructions .....	48-51
Frequently-Asked Questions .....	52
Warranty .....	53
Numerical Index .....	54



The manufacturing plants at Stuarts Draft, VA, Nacogdoches, TX and Reynosa, Mexico manufacture products under a Quality Management System conforming to the current revision of ISO-9001 International Standards

# Specifications

All of the advantages found in copper as a metal have been capitalized to the utmost in the manufacture of NIBCO Fittings. Because of the accuracy of construction and design, copper plumbing is more efficient and less expensive.

NIBCO manufactures nine general types of fittings: Wrot Pressure; Cast Pressure; Wrot Drainage; Cast Drainage; Flanges; Flared Tube; Threaded Bronze; Insert Fittings for PEX; Barbed Insert Fittings for Polybutylene. Each has its particular place and use and each offers its own advantages when used for the proper service requirement.

**ALLOY AND FINISH** — NIBCO Fittings are made from highest quality raw materials available — Cast Fittings are made from Copper Alloy C84400 which consists of 81% Copper, 7% Lead, 3% Tin, and 9% Zinc per ASTM Specification B584. Wrot Copper Fittings are made from commercially pure copper mill products per ASTM Specifications B75 Alloy C12200.

NIBCO fittings are produced to meet requirements of applicable standards wherever practicable.

NIBCO brand wrot and cast fittings are manufactured in the U.S.A. and Mexico. The manufacturing plants at Stuarts Draft, VA, Nacogdoches, TX and Reynosa, Mexico are registered to ISO 9002 quality standards.

Following is suggested phrasing to be incorporated in your specifications or bills of material for Copper Tube Fittings.

**WROT SOLDER JOINT FITTINGS** — “Wrot Solder Joint Fittings shall be produced to one of the following specifications:

1. Material and workmanship shall be in accordance with ASME/ANSI B16.22; Wrought Copper and Copper Alloy Solder Joint Pressure Fittings.”
2. The dimensional, material and workmanship shall meet the requirements of MSS SP-104; Wrought Copper Solder Joint Pressure Fittings.”
3. The dimensional, material and workmanship of 5”–12” copper fittings shall meet the requirements of MSS SP-109 “Welded Fabricated Copper Solder Joint Pressure Fittings.”
4. Certified to NSF/ANSI 61.

**CAST COPPER ALLOY SOLDER JOINT FITTINGS** — “Cast Copper Alloy Solder Joint Fittings shall be in accordance with ASME B16.18.”

**WROT DRAINAGE FITTINGS** — “Wrot Drainage Fittings shall be in accordance with ASME B16.29.”

**CAST COPPER ALLOY SOLDER JOINT DRAINAGE FITTINGS** — “Cast Copper Alloy Solder Joint Drainage Fittings shall be in accordance with ASME B16.23.”

**CAST COPPER ALLOY FLARED TUBE FITTINGS** — “Cast Copper Alloy Flared Tube Fittings shall be in accordance with ASME B16.26.

**CAST COPPER ALLOY FLANGES AND FLANGED FITTINGS**—

CLASS 150 — Cast Copper Alloy Flanges and Flanged Fittings shall meet the requirements of MSS SP-106 and/or the workmanship and dimensions of Federal Specifications WW-F-406 or ASME Std. B16.24.

CLASS 125 — Material, workmanship and dimensions of flanges shall be in accordance with MSS SP-106.

**CAST BRONZE THREADED FITTINGS** — “Cast Bronze Threaded Fittings shall be in accordance with ANSI/ASME B16.15.”

**POLYBUTYLENE COPPER INSERT TYPE VALVES AND FITTINGS** — “Wrot Copper Insert Fittings shall be manufactured per the following specifications: MSS SP-103 or ASTM F1380.”

NIBCO Copper Tube Fittings are all produced to above Standards. To simplify, write your specifications to read: “Copper Tube Fittings to be in accordance with specifications as outlined in NIBCO Catalog c-cf-0602.”

**WROT COPPER MEDICAL MEDICAL GAS SYSTEM COMPONENTS** — Wrot copper fittings that are to be installed in medical gas applications shall be prepared in accordance with NFPA 99, Health Care Facilities Gas and Vacuum Systems and the Compressed Gas Association, Pamphlet G4.1. Packaging shall be adequately protective and include labeling that identifies the preparer and states that the product has been cleaned and bagged for oxygen or med gas service.

For technical information and dimensions refer to the engineering section contained in this catalog.

## Wrot and Cast Pressure Fittings


**600 Series – Wrot**  
**700 Series – Cast**

Adapters.....	6-8
Air Chambers.....	8
Bulkhead Fittings.....	8
Bushings.....	8
Caps.....	9
Couplings.....	9-11
Crosses.....	11
Elbows.....	11-15
Fitting Reducers.....	15
Flanges.....	15-16
Plugs.....	16
Return Bends.....	16
Straps.....	16
Tees.....	16-20
Traps.....	20
Unions.....	21
Venturi.....	21
Y's.....	21




The manufacturing plants at Stuarts Draft, VA, Nacogdoches, TX and Reynosa, Mexico manufacture products under a Quality Management System conforming to the current revision of ISO-9001 International Standards

## ADAPTERS




603  
Adapter C x F – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1/8	0.03	13/32
1/8 x 1/4	0.03	1/2
1/4	0.03	5/8
1/4 x 3/8	0.05	21/32
3/8	0.04	11/16
3/8 x 1/2	0.09	29/32
3/8 x 1/4	0.03	9/16
1/2	0.09	27/32
1/2 x 3/4	0.14	1
1/2 x 3/8	0.04	17/32
1/2 x 1/4	0.05	1/2
5/8 x 3/4	0.12	29/32
5/8 x 1/2	0.11	3/4
3/4	0.15	29/32
3/4 x 1	0.21	1 1/8
3/4 x 1/2	0.10	5/8
1	0.24	31/32
1 x 1 1/4	0.28	1 7/32
1 x 3/4	0.19	25/32
1 x 1/2	0.24	5/8
1 1/4	0.33	1 3/32
1 1/4 x 1 1/2	0.40	1 1/4
1 1/4 x 1	0.27	31/32
1 1/2	0.44	1 1/8
1 1/2 x 2	0.50	1 1/32
2	0.63	1 3/32
2 x 1 1/2	0.74	1 3/16
2 1/2	1.13	–
3	1.94	–




703  
Adapter C x F – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1/4 x 1/2	0.13	27/32
1/2 x 1	0.30	1
3/4 x 1 1/4	0.55	1 1/8
3/4 x 3/8	0.17	3/4
1 x 1 1/2	0.68	1 3/32
1 1/4 x 1	0.27	31/32
1 1/4 x 3/4	0.29	3/4
1 1/2 x 2	0.78	1 1/32
1 1/2 x 1	0.37	25/32
1 1/2 x 1 1/4	0.47	1 1/4
2 x 1 1/4	0.76	27/32
2 1/2	1.62	1 3/8
3	2.34	1 1/2
4	4.05	1 9/16




603-2  
Fitting Adapter Ftg x F – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1/4	0.03	1 3/32
3/8	0.06	1 3/16
1/2	0.09	1 7/16
1/2 x 3/8	0.05	1 1/4
3/4	0.13	1 11/16
1	0.27	2 1/32
1 1/4	0.31	2 1/8
1 1/2	0.43	2 5/16
2	0.61	2 17/32




703-2  
Fitting Adapter Ftg x F – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1/2 x 1/4	0.11	1 7/32
3/4 x 1/2	0.12	1 9/16
1 x 3/4	0.38	1 31/32
1 x 1/2	0.15	1 7/16
2 1/2	1.65	2 15/16
3	2.47	3 1/4



703-5 Special  
Drop Adapter C x F – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1/2	0.16	3/4
3/4	0.24	31/32




703-5B  
Drop Adapter C x F – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1/2	0.15	3/4


Consult price sheet for Made to Order items and for minimum order quantities.

**ADAPTERS** *continued*




**604**  
Adapter C x M – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1/8 x 1/4	0.03	7/16
1/4	0.03	23/32
3/8	0.04	15/32
3/8 x 3/4	0.15	15/16
3/8 x 1/2	0.09	1
1/2	0.07	5/8
1/2 x 1	0.25	1 1/2
1/2 x 3/4	0.15	13/16
1/2 x 3/8	0.05	19/32
1/2 x 1/4	0.07	5/8
5/8 x 3/4	0.16	1 1/8
5/8 x 1/2	0.08	3/4
3/4	0.14	13/16
3/4 x 1	0.26	1 7/16
3/4 x 1/2	0.10	27/32
1	0.21	31/32
1 x 1 1/2	0.54	29/32
1 x 1 1/4	0.38	1 1/2
1 x 3/4	0.18	29/32
1 x 1/2	0.18	31/32
1 1/4	0.35	15/16
1 1/4 x 1 1/2	0.51	1 19/32
1 1/4 x 1	0.27	15/32
1 1/2	0.44	31/32
1 1/2 x 2	0.81	1 1/8
1 1/2 x 1 1/4	0.38	1 3/16
1 1/2 x 1	0.37	1 3/32
2	0.81	1 3/32
2 x 1 1/2	0.64	1 1/8
2 1/2	1.48	1 21/32
3	1.69	–




**704**  
Adapter C x M – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
3/4 x 1 1/2	0.60	1 17/32
3/4 x 1 1/4	0.38	1 7/32
3/4 x 3/8	0.19	13/16
1 x 2	1.15	–
1 x 1 1/2	0.64	29/32
1 1/4 x 2	0.88	1 9/32
1 1/4 x 3/4	0.30	31/32
1 1/2 x 2	0.77	1 1/8
2 x 2 1/2	1.57	1 15/32
2 x 1 1/2	0.71	1 1/8
2 x 1 1/4	1.08	–
2 1/2	1.48	1 21/32
2 1/2 x 2	1.83	1 11/16
3	1.96	1 1/2
4	3.66	1 11/16
5	8.60	2 5/8
6	10.73	2



**704-F**  
Flush Adapter C x M – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1/2	0.03	9/16
3/4	0.03	19/32



**704-H**  
Hose Adapter C x Hose – Cast


NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1/2	0.09	9/32

NOTE: Fits 1/2" 5/8" and 3/4" Garden Hose.



**604-2**  
Fitting Adapter Ftg x M – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1/8	0.02	1 1/8
3/8	0.04	1 1/4
1/2	0.09	1 15/32
1/2 x 3/4	0.16	1 13/16
1/2 x 3/8	0.04	1 11/32
3/4	0.17	1 15/16
1	0.25	2 1/4




**704-2**  
Fitting Adapter Ftg x M – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
3/4 x 1	0.27	1 31/32
3/4 x 1/2	0.12	1 23/32
1 x 3/4	0.24	1 15/16
1 1/4	0.43	2 27/32
1 1/2	0.54	2 13/32
2	0.89	2 3/4
2 1/2	1.55	3 3/8
3	2.21	3 23/32

Consult price sheet for Made to Order items and for minimum order quantities.



## ADAPTERS *continued*



704-2-H  
Hose Adapter Ftg x Hose – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
3/4 F x 3/4 H	0.16	1 <sup>5</sup> / <sub>8</sub>


NOTE: Fits 1/2", 5/8" and 3/4" Garden Hose.

## AIR CHAMBERS



619  
Air Chamber Ftg. – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. L INCHES
1/2 x 6	0.21	1	6
1/2 x 12	0.41	1	12
1/2 x 14	0.78	1 <sup>1</sup> / <sub>8</sub>	14
3/4 x 12	0.40	1	12




620-L  
Air Chamber or Stub-Out  
Ftg. – Wrot

As Air Chamber, just solder one joint. When used as Stub-Out, simply pressure test system then cut off stub-out (save piece for future use) and install valve or fixture.


NOM. SIZE	APPROX. NET WT./LBS.	DIM. L INCHES
1/2 x 6	0.14	6
1/2 x 8	0.19	8
1/2 x 10	0.24	10
1/2 x 12	0.28	12
3/4 x 12	0.46	12

## BULKHEAD FITTINGS




750  
Bulkhead Fitting C x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. B INCHES
1/2	0.48	1 <sup>1</sup> / <sub>4</sub>	1
3/4	0.77	1 <sup>9</sup> / <sub>32</sub>	1 <sup>1</sup> / <sub>4</sub>
1	1.30	1 <sup>1</sup> / <sub>2</sub>	1 <sup>5</sup> / <sub>8</sub>
1 1/2	2.87	1 <sup>1</sup> / <sub>2</sub>	2 <sup>3</sup> / <sub>8</sub>
2	3.82	2 <sup>1</sup> / <sub>32</sub>	2 <sup>5</sup> / <sub>8</sub>



750-3  
Bulkhead Fitting C x F – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. B INCHES
1/2	0.48	1 <sup>15</sup> / <sub>16</sub>	1
3/4	0.79	2 <sup>1</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>4</sub>
1	1.43	2 <sup>15</sup> / <sub>32</sub>	1 <sup>5</sup> / <sub>8</sub>



750-4  
Bulkhead Fitting C x M – Cast


NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. B INCHES
1/2	0.40	1 <sup>31</sup> / <sub>32</sub>	1
3/4	0.79	2 <sup>5</sup> / <sub>32</sub>	1 <sup>1</sup> / <sub>4</sub>

## BUSHINGS




618  
Flush Bushing Ftg x C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES
1/4 x 1/8	0.01	1 <sup>1</sup> / <sub>16</sub>
3/8 x 1/4	0.01	1 <sup>1</sup> / <sub>16</sub>
1/2 x 3/8	0.02	3 <sup>3</sup> / <sub>32</sub>
1/2 x 1/4	0.04	1 <sup>1</sup> / <sub>4</sub>
5/8 x 1/2	0.03	1 <sup>1</sup> / <sub>16</sub>
3/4 x 5/8	0.22	3 <sup>3</sup> / <sub>16</sub>
3/4 x 1/2	0.08	3 <sup>3</sup> / <sub>32</sub>
3/4 x 3/8	0.11	7 <sup>1</sup> / <sub>16</sub>
1 x 3/4	0.12	1 <sup>1</sup> / <sub>8</sub>
1 x 1/2	0.22	1 <sup>15</sup> / <sub>32</sub>
1 1/4 x 1	0.17	3 <sup>3</sup> / <sub>32</sub>
1 1/2 x 1 1/4	0.22	5 <sup>5</sup> / <sub>32</sub>
2 x 1 1/2	0.66	1 <sup>1</sup> / <sub>8</sub>



618-3  
Flush Bushing Ftg x F – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1/2 x 1/8	0.03	9 <sup>9</sup> / <sub>16</sub>
1/2 x 1/4	0.03	9 <sup>9</sup> / <sub>16</sub>




718-3  
Flush Bushing Ftg x F – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
3/4 x 3/8	0.06	1 <sup>31</sup> / <sub>32</sub>
1 x 1/2	0.13	3 <sup>1</sup> / <sub>32</sub>
1 1/4 x 3/4	0.18	1 <sup>1</sup> / <sub>32</sub>
1 1/2 x 1	0.25	1 <sup>5</sup> / <sub>32</sub>

Consult price sheet for Made to Order items and for minimum order quantities.




## CAPS




617  
Tube Cap C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. N INCHES
1/8	0.01	1/32
1/4	0.01	3/32
3/8	0.01	3/32
1/2	0.02	3/32
5/8	0.03	1/8
3/4	0.04	1/8
1	0.07	5/32
1 1/4	0.10	3/32
1 1/2	0.16	1/8
2	0.27	5/32
2 1/2	0.50	7/32
3	0.78	7/32
4	1.66	1/4



717  
Tube Cap C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. N INCHES
5	5.48	7/16
6	9.07	17/32




717-D  
Drain Cap – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1/2	0.06	21/32

Consult price sheet for Made to Order items and for minimum order quantities.

## COUPLINGS




600  
Reducing Coupling C x C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1/8 x 3/16 O.D.	0.01	5/32
5/16 O.D. x 1/8	0.01	3/16
1/4 x 5/16 O.D.	0.01	3/16
1/4 x 1/8	0.01	3/16
3/8 x 1/4	0.02	3/16
3/8 x 5/16 O.D.	0.01	1/4
3/8 x 1/8	0.01	1/4
1/2 x 3/8	0.03	3/16
1/2 x 1/4	0.02	1/4
1/2 x 1/8	0.03	11/32
5/8 x 1/2	0.05	3/16
5/8 x 3/8	0.04	11/32
5/8 x 1/4	0.03	13/32
3/4 x 5/8	0.07	3/16
3/4 x 1/2	0.06	9/32
3/4 x 3/8	0.06	3/8
3/4 x 1/4	0.05	11/32
1 x 3/4	0.11	11/32
1 x 5/8	0.09	3/8
1 x 1/2	0.10	11/32
1 x 3/8	0.10	13/32
1 1/4 x 1	0.16	5/16
1 1/4 x 3/4	0.18	17/32
1 1/4 x 5/8	0.18	5/8
1 1/4 x 1/2	0.14	7/16
1 1/2 x 1 1/4	0.23	5/16
1 1/2 x 1	0.22	9/16
1 1/2 x 3/4	0.20	3/8
1 1/2 x 1/2	0.19	1/2
2 x 1 1/2	0.41	9/16
2 x 1 1/4	0.35	11/16
2 x 1	0.37	7/16
2 x 3/4	0.34	17/32
2 x 1/2	0.35	23/32
2 1/2 x 2	0.59	9/16
2 1/2 x 1 1/2	0.65	11/16
2 1/2 x 1 1/4	0.65	13/16
2 1/2 x 1	0.73	29/32

Continues...


NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
3 x 2 1/2	0.98	1/2
3 x 2	1.06	15/16
3 x 1 1/2	0.92	11/32
3 1/2 x 3	1.52	1/2
4 x 3 1/2	2.12	19/32
4 x 3	1.92	27/32
4 x 2 1/2	1.77	1
4 x 2	1.92	1 1/4
5 x 4	3.50	3 31/32
5 x 3	3.18	1 15/32
5 x 2 1/2	3.50	1 3/16
5 x 2	3.09	2 1/32
6 x 5	5.70	1 1/8
6 x 4	5.24	1 1/2
6 x 3	5.04	2
6 x 2 1/2	5.13	2 1/4
6 x 2	4.89	2 1/2
8 x 6	13.06	1 19/32
8 x 4	12.22	2 19/32
8 x 3	11.79	3 3/32
8 x 2 1/2	12.64	3 3/8



600-RS  
Coupling with Rolled Tube Stop  
C x C – Wrot


NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1/8 O.D.	0.01	1/16
3/16 O.D.	0.01	3/32
1/8	0.01	1/16
5/16 O.D.	0.01	3/32
1/4	0.01	1/16
3/8	0.01	3/32
1/2	0.03	3/32
5/8	0.04	3/32
3/4	0.06	3/32
7/8	0.09	3/32
1	0.11	3/32
1 1/4	0.16	1/8
1 1/2	0.23	1/8
2	0.41	1/8
2 1/2	0.65	1/8
3	0.93	1/8
3 1/2	1.45	5/32
4	1.93	7/32

**COUPLINGS** *continued*




**600-DS**  
Coupling with Dimpled Tube Stop  
C x C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
3/16 O.D.	0.01	3/32
1/8	0.01	1/16
5/16 O.D.	0.01	3/32
1/4	0.01	1/16
3/8	0.01	3/32
1/2	0.03	3/32
5/8	0.04	3/32
3/4	0.06	3/32
7/8	0.09	3/32
1	0.11	3/32
1 1/4	0.16	1/8
1 1/2	0.23	1/8
2	0.41	1/8
2 1/2	0.65	1/8
3	0.93	1/8
3 1/2	1.45	5/32
4	1.93	7/32
5	3.53	7/32
6	5.63	7/32
8	14.12	15/32




**601**  
Coupling without Stop  
C x C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1/4	0.01	11/16
3/8	0.01	27/32
1/2	0.03	1
5/8	0.04	1 11/32
3/4	0.06	1 19/32
1	0.11	1 29/32
1 1/4	0.16	2 1/16
1 1/2	0.23	2 5/16
2	0.41	2 13/16
2 1/2	0.64	2 15/16
3	0.86	3 5/16
3 1/2	1.40	3 13/16
4	1.84	4 5/16
5	3.50	5 5/16
6	5.60	6 3/16
8	13.68	8 3/32




**701**  
Reducing Coupling C x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
3 x 1 1/4	1.35	23/32
3 x 1	1.64	27/32




**701-D**  
Drain Coupling C x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1/2	0.08	1/4
3/4	0.14	1/4
1	0.22	1/4



**702**  
Eccentric Coupling C x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
3/4 x 1/2	0.10	17/32
1 x 3/4	0.18	1/4
1 1/4 x 1	0.25	1/4
1 1/4 x 3/4	0.24	9/32




**724-5-A**  
Hy-Set Hanger Coupling  
C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES	DIM. D INCHES
1/2	0.05	1 5/8	23/32
3/4	0.09	1 5/8	27/32
1	0.13	1 5/8	1

Consult price sheet for Made to Order items and for minimum order quantities.


**COUPLINGS** *continued*



736  
Cross-Over Coupling  
C x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1/2	0.27	1 <sup>7</sup> / <sub>16</sub>
3/4	0.60	1 <sup>29</sup> / <sub>32</sub>


**CROSSES**



735  
Cross C x C x C x C – Cast



NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
3/8	0.09	3/8
1/2	0.15	7/16
3/4	0.30	9/16
1	0.54	2 <sup>3</sup> / <sub>32</sub>
1 1/4	0.78	7/8
1 1/2	1.05	1
2	2.00	1 <sup>1</sup> / <sub>4</sub>
2 1/2	2.96	1 <sup>1</sup> / <sub>2</sub>

**ELBOWS**



606  
45° Elbow C x C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES	DIM. D INCHES
1/8	0.01	1/4	1/4
1/4	0.02	9/32	9/32
3/8	0.03	3/16	3/16
1/2	0.04	9/32	9/32
5/8	0.09	15/32	15/32
3/4	0.10	11/32	11/32
7/8	0.20	11/16	11/16
1	0.16	3/8	3/8
1 1/4	0.25	17/32	17/32
1 1/2	0.35	19/32	19/32
2	0.65	25/32	25/32
2 1/2	1.07	29/32	29/32
3	1.58	1 <sup>1</sup> / <sub>8</sub>	1 <sup>1</sup> / <sub>8</sub>
4	3.35	1 <sup>7</sup> / <sub>16</sub>	1 <sup>7</sup> / <sub>16</sub>
5	11.05	1 <sup>9</sup> / <sub>16</sub>	1 <sup>9</sup> / <sub>16</sub>
6	16.95	2	2
8	23.00	2 <sup>9</sup> / <sub>32</sub>	2 <sup>9</sup> / <sub>32</sub>




606-2  
45° Fitting Elbow Ftg x C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES	DIM. C INCHES
1/4	0.02	9/16	1/4
1/2	0.04	3/4	7/32
5/8	0.08	1 <sup>1</sup> / <sub>8</sub>	13/32
3/4	0.10	1 <sup>1</sup> / <sub>16</sub>	5/16
1	0.16	1 <sup>7</sup> / <sub>32</sub>	15/32
1 1/4	0.25	1 <sup>19</sup> / <sub>32</sub>	17/32
1 1/2	0.35	1 <sup>25</sup> / <sub>32</sub>	19/32
2	0.65	2 <sup>3</sup> / <sub>16</sub>	25/32
2 1/2	1.07	2 <sup>3</sup> / <sub>16</sub>	29/32
3	1.55	2 <sup>19</sup> / <sub>32</sub>	1 <sup>5</sup> / <sub>32</sub>


Consult price sheet for Made to Order items and for minimum order quantities.

**ELBOWS** *continued*




706-2  
45° Fitting Elbow Ftg x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES	DIM. C INCHES
4	4.31	3 <sup>11</sup> / <sub>32</sub>	1 <sup>5</sup> / <sub>16</sub>




607  
90° Elbow – Close Rough  
C x C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES	DIM. D INCHES
1/8	0.01	1 <sup>3</sup> / <sub>32</sub>	1 <sup>3</sup> / <sub>32</sub>
1/4	0.02	9 <sup>9</sup> / <sub>32</sub>	9 <sup>9</sup> / <sub>32</sub>
3/8	0.03	1 <sup>1</sup> / <sub>2</sub>	1 <sup>1</sup> / <sub>2</sub>
1/2	0.04	3 <sup>3</sup> / <sub>8</sub>	3 <sup>3</sup> / <sub>8</sub>
1/2 x 3/8	0.04	9 <sup>9</sup> / <sub>16</sub>	2 <sup>1</sup> / <sub>32</sub>
3/4	0.10	1 <sup>7</sup> / <sub>32</sub>	1 <sup>7</sup> / <sub>32</sub>
3/4 x 5/8	0.12	2 <sup>9</sup> / <sub>32</sub>	7 <sup>7</sup> / <sub>8</sub>
3/4 x 1/2	0.10	1 <sup>7</sup> / <sub>32</sub>	3 <sup>3</sup> / <sub>4</sub>
1	0.21	2 <sup>3</sup> / <sub>32</sub>	2 <sup>3</sup> / <sub>32</sub>
1 x 3/4	0.16	2 <sup>3</sup> / <sub>32</sub>	5 <sup>5</sup> / <sub>8</sub>
1 1/4	0.31	1 <sup>1</sup> / <sub>32</sub>	1 <sup>1</sup> / <sub>32</sub>
1 1/4 x 1	0.31	1 <sup>5</sup> / <sub>8</sub>	1 <sup>15</sup> / <sub>32</sub>
1 1/2	0.46	1 <sup>7</sup> / <sub>32</sub>	1 <sup>7</sup> / <sub>32</sub>
1 1/2 x 1 1/4	0.35	1 <sup>5</sup> / <sub>32</sub>	1 <sup>3</sup> / <sub>32</sub>
2	0.84	1 <sup>1</sup> / <sub>2</sub>	1 <sup>1</sup> / <sub>2</sub>
2 x 1 1/2	0.58	1 <sup>7</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>4</sub>
2 1/2	1.41	1 <sup>27</sup> / <sub>32</sub>	1 <sup>27</sup> / <sub>32</sub>
3	2.07	2 <sup>3</sup> / <sub>32</sub>	2 <sup>3</sup> / <sub>32</sub>
3 1/2	2.94	2 <sup>3</sup> / <sub>8</sub>	2 <sup>3</sup> / <sub>8</sub>
4	4.23	2 <sup>25</sup> / <sub>32</sub>	2 <sup>25</sup> / <sub>32</sub>
5	7.74	2 <sup>7</sup> / <sub>8</sub>	2 <sup>7</sup> / <sub>8</sub>
6	10.95	3 <sup>7</sup> / <sub>16</sub>	3 <sup>7</sup> / <sub>16</sub>
8	29.50	4 <sup>23</sup> / <sub>32</sub>	4 <sup>23</sup> / <sub>32</sub>




707  
90° Elbow – Close Rough  
C x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES	DIM. D INCHES
1 1/4 x 1	0.42	1 <sup>5</sup> / <sub>8</sub>	1 <sup>15</sup> / <sub>32</sub>
1 1/4 x 3/4	0.34	9 <sup>9</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>16</sub>
1 1/4 x 1/2	0.28	1 <sup>5</sup> / <sub>32</sub>	2 <sup>7</sup> / <sub>32</sub>
1 1/2 x 1	0.54	1 <sup>11</sup> / <sub>16</sub>	1
1 1/2 x 3/4	0.42	1 <sup>9</sup> / <sub>32</sub>	3 <sup>1</sup> / <sub>32</sub>
1 1/2 x 1/2	0.40	5 <sup>5</sup> / <sub>8</sub>	2 <sup>9</sup> / <sub>32</sub>
2 x 1 1/4	0.86	7 <sup>7</sup> / <sub>8</sub>	1 <sup>1</sup> / <sub>4</sub>
2 x 1	0.78	3 <sup>3</sup> / <sub>4</sub>	1 <sup>1</sup> / <sub>4</sub>
2 x 3/4	0.69	5 <sup>5</sup> / <sub>8</sub>	1 <sup>1</sup> / <sub>4</sub>
2 1/2 x 2	2.16	1 <sup>3</sup> / <sub>16</sub>	1 <sup>9</sup> / <sub>32</sub>
3 x 2 1/2	2.26	1 <sup>11</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>2</sub>
3 x 2	2.68	1 <sup>3</sup> / <sub>8</sub>	1 <sup>9</sup> / <sub>16</sub>
4 x 3	5.18	1 <sup>29</sup> / <sub>32</sub>	2 <sup>15</sup> / <sub>32</sub>



607-1  
90° Elbow – Intermediate Radius  
C x C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES	DIM. D INCHES
1/2	0.06	1 <sup>9</sup> / <sub>32</sub>	1 <sup>9</sup> / <sub>32</sub>
5/8	0.09	7 <sup>7</sup> / <sub>8</sub>	7 <sup>7</sup> / <sub>8</sub>
3/4	0.14	1 <sup>3</sup> / <sub>16</sub>	3 <sup>3</sup> / <sub>16</sub>
1	0.24	1 <sup>1</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>16</sub>




607-LT  
90° Elbow – Long Radius  
C x C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES	DIM. D INCHES
3/16 O.D.	0.01	1 <sup>3</sup> / <sub>32</sub>	1 <sup>3</sup> / <sub>32</sub>
1/8	0.01	1 <sup>3</sup> / <sub>32</sub>	1 <sup>3</sup> / <sub>32</sub>
5/16 O.D.	0.02	9 <sup>9</sup> / <sub>16</sub>	9 <sup>9</sup> / <sub>16</sub>
1/4	0.02	1 <sup>7</sup> / <sub>32</sub>	1 <sup>7</sup> / <sub>32</sub>
1/4 x 1/8	0.01	1 <sup>9</sup> / <sub>32</sub>	1 <sup>1</sup> / <sub>2</sub>
3/8	0.04	2 <sup>3</sup> / <sub>32</sub>	2 <sup>3</sup> / <sub>32</sub>
1/2	0.08	7 <sup>7</sup> / <sub>8</sub>	7 <sup>7</sup> / <sub>8</sub>
1/2 x 3/8	0.06	1 <sup>3</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>16</sub>
1/2 x 1/4	0.03	2 <sup>5</sup> / <sub>32</sub>	2 <sup>1</sup> / <sub>32</sub>
5/8	0.10	1 <sup>3</sup> / <sub>32</sub>	1 <sup>3</sup> / <sub>32</sub>
5/8 x 1/2	0.09	1 <sup>1</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>16</sub>
3/4	0.16	1 <sup>1</sup> / <sub>8</sub>	1 <sup>1</sup> / <sub>8</sub>
3/4 x 5/8	0.13	1 <sup>1</sup> / <sub>4</sub>	1 <sup>3</sup> / <sub>32</sub>
3/4 x 1/2	0.10	1 <sup>1</sup> / <sub>8</sub>	1 <sup>1</sup> / <sub>16</sub>
7/8	0.28	1 <sup>19</sup> / <sub>32</sub>	1 <sup>19</sup> / <sub>32</sub>
1	0.28	1 <sup>7</sup> / <sub>16</sub>	1 <sup>7</sup> / <sub>16</sub>
1 x 3/4	0.20	1 <sup>1</sup> / <sub>4</sub>	1 <sup>1</sup> / <sub>8</sub>
1 x 5/8	0.15	1 <sup>13</sup> / <sub>32</sub>	1 <sup>3</sup> / <sub>32</sub>
1 1/4	0.42	1 <sup>7</sup> / <sub>8</sub>	1 <sup>7</sup> / <sub>8</sub>
1 1/4 x 1	0.33	1 <sup>25</sup> / <sub>32</sub>	1 <sup>1</sup> / <sub>2</sub>
1 1/2	0.66	2 <sup>1</sup> / <sub>4</sub>	2 <sup>1</sup> / <sub>4</sub>
2	1.23	2 <sup>15</sup> / <sub>16</sub>	2 <sup>15</sup> / <sub>16</sub>
2 1/2	1.96	3 <sup>11</sup> / <sub>16</sub>	3 <sup>11</sup> / <sub>16</sub>
3	2.93	4 <sup>1</sup> / <sub>32</sub>	4 <sup>1</sup> / <sub>32</sub>
4	5.95	5 <sup>1</sup> / <sub>4</sub>	5 <sup>1</sup> / <sub>4</sub>


Consult price sheet for Made to Order items and for minimum order quantities.

**ELBOWS** *continued*




**607-2**  
90° Fitting Elbow – Close Rough  
Ftg x C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES	DIM. C INCHES
1/4	0.02	3/4	3/8
3/8	0.03	15/16	1/2
1/2	0.04	31/32	3/8
5/8	0.07	17/32	17/32
3/4	0.10	111/32	17/32
1	0.20	13/4	27/32
1 1/4	0.33	21/8	11/32
1 1/2	0.46	213/32	17/32
2	0.84	227/32	11/2
2 1/2	1.39	315/32	129/32
3	2.10	313/16	23/32
4	4.00	43/4	225/32




**607-2-1**  
90° Fitting Elbow – Intermediate Radius  
Ftg x C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES	DIM. C INCHES
1/2	0.06	15/32	19/32
5/8	0.09	19/16	7/8
3/4	0.14	15/8	13/16
1	0.24	21/32	11/16




**607-2-LT**  
90° Fitting Elbow – Long Radius  
Ftg x C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES	DIM. C INCHES
1/8	0.01	13/32	1/2
1/4	0.02	11/8	3/4
3/8	0.05	11/8	7/8
1/2	0.08	19/16	13/32
1/2 x 3/8	0.06	15/16	13/16
1/2 x 1/4	0.03	11/4	5/8
5/8	0.10	125/32	13/32
3/4	0.16	115/16	11/8
1	0.31	21/2	121/32
1 1/4	0.43	229/32	17/8
1 1/2	0.66	213/32	21/4
1 1/2 x 1 1/4	0.50	33/8	23/32
2	1.27	411/32	231/32
2 1/2	2.16	57/32	311/16
3	3.10	53/4	41/32




**607-2-2**  
90° Fitting Elbow – Close Rough  
Ftg x Ftg – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1/2	0.04	11/16
3/4	0.12	115/32
1	0.20	123/32
1 1/4	0.33	21/8
1 1/2	0.46	213/32
2	0.82	227/32
3	2.12	37/8



**607-2-2-LT**  
90° Fitting Elbow – Long Radius  
Ftg x Ftg – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1/4	0.02	27/32
3/8	0.04	11/8
1/2	0.08	119/32
5/8	0.10	111/16
3/4	0.16	115/16
1	0.31	21/2
1 1/4	0.43	229/32
1 1/2	0.65	37/16
2	1.25	411/32




**707-2-4**  
90° Fitting Elbow  
Ftg x M – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES	DIM. E INCHES
1/2	0.12	7/8	25/32


Consult price sheet for Made to Order items and for minimum order quantities.

**ELBOWS** *continued*




**707-3**  
90° Elbow C x F – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES	DIM. E INCHES
1/4	0.06	13/32	9/16
3/8	0.09	7/16	11/16
3/8 x 1/2	0.13	9/16	13/16
1/2	0.12	7/16	13/16
1/2 x 3/4	0.18	11/16	15/16
1/2 x 3/8	0.09	1/2	13/16
1/2 x 1/4	0.10	3/8	23/32
3/4	0.18	21/32	15/16
3/4 x 1	0.35	13/16	1 1/8
3/4 x 1/2	0.20	9/16	15/16
1	0.43	25/32	1 1/4
1 x 3/4	0.35	11/16	1 3/16
1 x 1/2	0.26	9/16	1 1/8
1 1/4	0.67	1	1 1/2
1 1/4 x 3/4	0.47	9/16	1 11/16
1 1/2	0.89	1 1/8	1 5/8
2	1.46	1 3/8	1 15/16




**707-3-5-A**  
90° Hy-Set Elbow C x F – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES	DIM. E INCHES
1/2	0.21	9/16	7/8




**707-3-6**  
90° Union Elbow C x F – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. E INCHES
1/2	0.31	1 1/8	7/8
3/4	0.49	1 7/16	1
1	0.79	1 7/8	1 1/4




**707-4-6**  
90° Union Elbow C x M – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. E INCHES
3/8	0.21	13/32	13/16
1/2	0.30	1 1/32	1 1/2
3/4	0.49	15/16	1 13/16
1	0.72	1 23/32	1 5/8
1 1/4	1.16	1 3/4	1 27/32




**707-5**  
90° Drop Elbow C x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. C INCHES
1/2	0.13	13/32	7/16
3/4	0.24	17/32	9/16




**707-3-5**  
90° Drop Elbow C x F – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. C INCHES	DIM. E INCHES
3/8	0.12	11/32	7/16	11/16
3/8 x 1/2	0.18	11/32	9/16	13/16
1/2	0.15	13/32	9/16	7/8
1/2 x 3/8	0.17	3/8	1/2	13/16
3/4	0.28	17/32	21/32	15/16
3/4 x 1/2	0.24	17/32	9/16	15/16
1	0.49	5/8	25/32	1 1/4



**707-4**  
90° Elbow C x M – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES	DIM. E INCHES
3/8	0.08	5/16	7/8
1/2	0.12	7/16	1 5/32
1/2 x 3/4	0.18	9/16	1 5/32
1/2 x 3/8	0.10	5/16	15/16
3/4	0.21	9/16	1 11/32
3/4 x 1	0.33	21/32	1 13/32
3/4 x 1/2	0.18	7/16	1 7/32
1	0.43	23/32	1 5/8
1 1/4	0.58	7/8	1 11/16
1 1/2	0.81	1	1 31/32
2	1.38	1 1/4	2 9/32




**707-5-A**  
90° Hy-Set Elbow C x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. C INCHES	DIM. D INCHES
1/2	0.13	31/32	7/16	15/32
3/4	0.21	15/16	9/16	9/16

Consult price sheet for Made to Order items and for minimum order quantities.





## ELBOWS *continued*





707-6  
90° Union Elbow C x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. C INCHES
3/8	0.17	31/32	5/16
1/2	0.24	1	7/16
3/4	0.39	1 17/32	9/16
1	0.64	1 21/32	23/32
1 1/4	1.07	1 19/32	23/32



708  
90° Flanged Sink Elbow  
C x F – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. C INCHES	DIM. F INCHES
1/2	0.20	7/8	9/16	1 3/4




764  
90° Double Elbow  
C x C x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES	DIM. D INCHES
1 x 3/4 x 3/4	0.33	3/4	21/32

Consult price sheet for Made to Order items and for minimum order quantities.

## FITTING REDUCERS




600-2  
Fitting Reducer Ftg x C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1/4 x 1/8	0.01	15/32
3/8 x 1/4	0.01	19/32
3/8 x 1/8	0.01	25/32
1/2 x 3/8	0.03	11/16
1/2 x 1/4	0.02	25/32
5/8 x 1/2	0.04	7/8
5/8 x 3/8	0.04	31/32
5/8 x 1/4	0.03	1 1/32
3/4 x 5/8	0.06	31/32
3/4 x 1/2	0.06	1 1/8
3/4 x 3/8	0.05	1 1/8
3/4 x 1/4	0.05	1 3/32
1 x 3/4	0.10	1 7/32
1 x 5/8	0.09	1 3/8
1 x 1/2	0.09	1 1/4
1 x 3/8	0.08	1 9/32
1 1/4 x 1	0.15	1 5/16
1 1/4 x 3/4	0.16	1 1/2
1 1/4 x 1/2	0.13	1 3/8
1 1/2 x 1 1/4	0.23	1 13/32
1 1/2 x 1	0.21	1 5/8
1 1/2 x 3/4	0.20	1 7/8
1 1/2 x 1/2	0.16	1 19/32
2 x 1 1/2	0.40	1 31/32
2 x 1 1/4	0.34	2 3/32
2 x 1	0.35	1 27/32
2 x 3/4	0.35	1 27/32
2 x 1/2	0.34	1 31/32
2 1/2 x 2	0.65	1 31/32
2 1/2 x 1 1/2	0.65	2 3/8
2 1/2 x 1 1/4	0.60	2 7/32
2 1/2 x 1	0.78	2 9/32
3 x 2 1/2	1.03	2 1/4
3 x 2	0.99	2 9/16
3 x 1 1/2	0.81	2 19/32
3 x 1 1/4	1.29	3 1/4
3 1/2 x 3	1.48	2 11/32

Continues...

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
4 x 3 1/2	2.09	2 5/8
4 x 3	2.00	3 1/32
4 x 2 1/2	1.56	3 1/32
4 x 2	1.76	3 13/32
5 x 4	3.30	3 9/16
5 x 3	2.97	4 1/16
5 x 2 1/2	3.30	4 11/32
5 x 2	2.88	4 11/16
6 x 5	5.56	4 3/16
6 x 4	5.09	4 9/16
6 x 3	4.67	5 1/16
6 x 2 1/2	4.47	5 11/32
6 x 2	4.51	5 19/32
8 x 6	12.33	5 15/32
8 x 5	10.35	5 15/16
8 x 4	11.10	6 7/16
8 x 3	10.63	6 15/16
8 x 2 1/2	11.41	7 3/16
8 x 2	10.86	7 7/16

## FLANGES – CLASS 125




741  
Companion Flange C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES	DIM. F INCHES	DIM. G INCHES	DIM. W INCHES
1/2	0.55	1/8	3 1/2	3/16	2 3/8
3/4	0.71	1/8	3 7/8	3/16	2 3/4
1	1.26	1/8	4 1/4	1/4	3 1/8
1 1/4	1.42	1/8	4 5/8	1/4	3 1/2
1 1/2	1.82	1/8	5	5/16	3 7/8
2	2.76	1/8	6	3/8	4 3/4
2 1/2	4.29	1/8	7	3/8	5 1/2
3	5.26	1/8	7 1/2	7/16	6
4	7.60	1/8	9	7/16	7 1/2
5	9.04	1/8	10	7/16	8 1/2
6	12.68	1/8	11	1/2	9 1/2

NOTE: Dim. B = Tube Stop to Flange Face




## FLANGES – CLASS 150



771  
Companion Flange C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES	DIM. F INCHES	DIM. G INCHES	DIM. W INCHES
3/4	1.15	1/8	3 7/8	1 1/32	2 3/4
1	1.59	1/8	4 1/4	3/8	3 1/8
1 1/4	1.91	1/8	4 5/8	13/32	3 1/2
1 1/2	2.59	1/8	5	7/16	3 7/8
2	4.10	1/8	6	1/2	4 3/4
2 1/2	6.22	1/8	7	9/16	5 1/2
3	8.03	1/8	7 1/2	5/8	6
4	11.85	1/8	9	1 1/16	7 1/2
5	15.69	1/8	10	3/4	8 1/2
6	20.32	1/8	11	13/16	9 1/2


NOTE: Dim. B = Tube Stop to Flange Face



775  
Threaded Companion Flange F – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. E INCHES	DIM. F INCHES	DIM. W INCHES
2	4.31	1	6	4 3/4
2 1/2	6.30	1 1/8	7	5 1/2
3	7.13	1 3/16	7 1/2	6
4	10.20	1 5/16	9	7 1/2


## PLUGS



616  
Fitted Plug Ftg - Wrot


NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
3/8	0.016	1/16
1/2	0.02	3/32
3/4	0.24	1/8

## RETURN BENDS



638  
Return Bend C x C – Wrot


NOM. SIZE	APPROX. NET WT./LBS.	DIM. E INCHES	DIM. J INCHES
1/8	0.02	2 1/32	1
1/4	0.04	2 1/32	1 1/2
3/8	0.08	1 1/32	1 1/2
1/2	0.13	1 1/2	2
3/4	0.26	1 19/32	2 1/2
1	0.44	2 3/32	3
1 1/4	0.70	2 3/4	4
1 1/2	1.04	3 5/32	4 1/2
2	1.92	3 29/32	5 1/2



739  
Return Bend – Closed C x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. E INCHES	DIM. J INCHES
3/4	0.29	1 5/32	1 5/16

## STRAPS



623  
Copper Hanger Strap


SIZE	APPROX. NET WT./LBS.
3/4" Wide x 25 Ft. Roll	1.93



624  
Tube Strap

NOM. SIZE	APPROX. NET WT./LBS.
1/8	0.01
1/4	0.01
3/8	0.01
1/2	0.01
5/8	0.02
3/4	0.02
1	0.02
1 1/4	0.03
1 1/2	0.03
2	0.04

## TEES




705  
Baseboard Tee C x F x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIMENSIONS INCHES		
		C	D	E
1/2 x 1/8 x 3/4	0.15	7/16	9/16	1 1/16
1/2 x 1/8 x 1/2	0.11	7/16	7/16	9/16
3/4 x 1/8 x 1	0.29	5/8	3/4	13/16
3/4 x 1/8 x 3/4	0.19	9/16	9/16	1 1/16
1 x 1/8 x 1	0.32	23/32	23/32	3/4
1 1/4 x 1/8 x 1 1/4	0.51	7/8	7/8	1 5/16


Consult price sheet for Made to Order items and for minimum order quantities.

**TEES** *continued*




**705-D**  
Vent Elbow C x C – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		C	D	S
1/2	0.10	7/16	7/16	25/32
3/4	0.20	9/16	9/16	29/32
1	0.31	23/32	23/32	11/32




**710-3**  
Tee F x F x C – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		C	E	S
1/2	0.20	9/16	7/8	7/8
3/4	0.37	11/16	1	1
3/4 x 3/4 x 1/2	0.31	11/16	31/32	31/32
3/4 x 1/2 x 3/4	0.29	11/16	1	15/16
3/4 x 1/2 x 1/2	0.27	11/16	31/32	7/8



**710-3-4**  
Tee M x F x C – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		C	E	S
3/4	0.34	11/16	11/32	1
3/4 x 3/4 x 1/2	0.33	11/16	17/32	31/32



**611**  
Tee C x C x C – Wrot

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		C	F	G
3/16 <sub>O.D.</sub>	0.01	7/32	7/32	7/32
1/8	0.02	1/4	1/4	7/32
1/8 x 1/8 x 1/4	0.02	13/32	13/32	1/4
1/8 x 1/8 x 3/16 <sub>O.D.</sub>	0.01	1/4	1/4	5/16
1/8 x 3/16 <sub>O.D.</sub> x 1/8	0.01	1/4	11/32	7/32
5/16 <sub>O.D.</sub>	0.02	3/8	3/8	5/16
5/16 <sub>O.D.</sub> x 5/16 <sub>O.D.</sub> x 1/4	0.02	3/8	3/8	1/4
5/16 <sub>O.D.</sub> x 5/16 <sub>O.D.</sub> x 1/8	0.02	3/8	3/8	13/32
5/16 <sub>O.D.</sub> x 1/8 x 5/16 <sub>O.D.</sub>	0.02	3/8	13/32	5/16
5/16 <sub>O.D.</sub> x 1/8 x 1/8	0.02	3/8	13/32	13/32
1/4	0.02	5/16	5/16	1/4
1/4 x 1/4 x 1/2	0.06	19/32	19/32	3/8
1/4 x 1/4 x 3/8	0.04	17/32	17/32	11/32
1/4 x 1/4 x 5/16 <sub>O.D.</sub>	0.02	5/16	5/16	5/16
1/4 x 1/4 x 1/8	0.02	5/16	5/16	13/32
1/4 x 1/4 x 3/16 <sub>O.D.</sub>	0.02	5/16	5/16	7/16
1/4 x 5/16 <sub>O.D.</sub> x 1/4	0.02	5/16	3/8	1/4
1/4 x 1/8 x 1/4	0.02	5/16	13/32	1/4
1/4 x 1/8 x 1/8	0.02	5/16	13/32	3/8
3/8	0.04	11/32	11/32	11/32
3/8 x 3/8 x 1/2	0.07	17/32	17/32	3/8
3/8 x 3/8 x 1/4	0.04	11/32	11/32	15/32
3/8 x 3/8 x 5/16 <sub>O.D.</sub>	0.04	11/32	11/32	11/32
3/8 x 3/8 x 1/8	0.04	11/32	11/32	11/32
3/8 x 1/4 x 3/8	0.04	11/32	17/32	11/32
3/8 x 1/4 x 1/4	0.04	11/32	17/32	15/32
3/8 x 1/4 x 1/8	0.04	11/32	17/32	9/16
3/8 x 1/8 x 3/8	0.04	11/32	19/32	11/32
3/8 x 1/8 x 1/8	0.04	11/32	19/32	19/32
1/2	0.06	11/32	11/32	11/32
1/2 x 1/2 x 1	0.29	1	1	21/32
1/2 x 1/2 x 3/4	0.12	17/32	17/32	11/32
1/2 x 1/2 x 5/8	0.11	5/8	5/8	7/16
1/2 x 1/2 x 3/8	0.07	5/16	5/16	13/32
1/2 x 1/2 x 1/4	0.06	5/16	5/16	9/16
1/2 x 3/8 x 1/2	0.07	7/16	17/32	3/8
1/2 x 3/8 x 3/8	0.06	5/16	17/32	13/32
1/2 x 3/8 x 1/4	0.06	5/16	17/32	17/32
1/2 x 1/4 x 3/8	0.06	5/16	5/8	9/16

NOTE: Tee sizes are read Run x Run x Outlet.


NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		C	F	G
5/8	0.12	7/16	7/16	7/16
5/8 x 5/8 x 3/4	0.15	23/32	23/32	1/2
5/8 x 5/8 x 1/2	0.11	7/16	7/16	13/32
5/8 x 5/8 x 3/8	0.09	7/16	7/16	5/8
5/8 x 5/8 x 1/4	0.09	7/16	7/16	3/4
5/8 x 1/2 x 5/8	0.10	7/16	5/8	7/16
5/8 x 1/2 x 1/2	0.09	7/16	19/32	13/32
5/8 x 3/8 x 5/8	0.10	7/16	3/4	7/16
5/8 x 3/8 x 3/8	0.09	7/16	3/4	5/8
3/4	0.15	1/2	1/2	1/2
3/4 x 3/4 x 1	0.22	23/32	23/32	1/2
3/4 x 3/4 x 5/8	0.16	17/32	17/32	11/16
3/4 x 3/4 x 1/2	0.12	7/16	7/16	17/32
3/4 x 3/4 x 3/8	0.12	7/16	7/16	21/32
3/4 x 3/4 x 1/4	0.12	13/32	13/32	23/32
3/4 x 3/4 x 1/8	0.12	7/16	7/16	13/16
3/4 x 5/8 x 3/4	0.15	17/32	11/16	1/2
3/4 x 5/8 x 5/8	0.15	17/32	23/32	11/16
3/4 x 1/2 x 3/4	0.15	17/32	25/32	1/2
3/4 x 1/2 x 1/2	0.12	13/32	19/32	1/2
3/4 x 1/2 x 3/8	0.12	7/16	21/32	21/32
3/4 x 3/8 x 3/4	0.15	17/32	17/32	1/2
3/4 x 3/8 x 1/2	0.12	7/16	23/32	17/32
3/4 x 3/8 x 3/8	0.12	7/16	23/32	21/32
7/8	0.31	23/32	23/32	23/32
1	0.30	11/16	11/16	21/32
1 x 1 x 1 1/2	0.60	111/32	111/32	31/32
1 x 1 x 1 1/4	0.42	1	1	29/32
1 x 1 x 3/4	0.27	9/16	9/16	21/32
1 x 1 x 5/8	0.26	9/16	9/16	7/8
1 x 1 x 1/2	0.23	15/32	15/32	23/32
1 x 1 x 3/8	0.23	15/32	15/32	29/32
1 x 1 x 1/4	0.23	15/32	15/32	1
1 x 3/4 x 1	0.29	11/16	7/8	21/32
1 x 3/4 x 3/4	0.26	9/16	23/32	3/4
1 x 3/4 x 1/2	0.22	15/32	21/32	23/32

*Continues...*

*Continues...*

Consult price sheet for Made to Order items and for minimum order quantities.

**TEES** *continued*



**611**  
Tee C x C x C – Wrot continued

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		C	F	G
1 x 1/2 x 1	0.29	11/16	1	21/32
1 x 1/2 x 3/4	0.27	9/16	13/16	3/4
1 x 1/2 x 1/2	0.22	15/32	25/32	23/32
1 1/4	0.43	13/16	3/16	13/16
1 1/4 x 1 1/4 x 2	1.13	130/32	130/32	13/32
1 1/4 x 1 1/4 x 1 1/2	0.60	13/16	13/16	29/32
1 1/4 x 1 1/4 x 1	0.45	25/32	25/32	29/32
1 1/4 x 1 1/4 x 3/4	0.37	21/32	21/32	3/4
1 1/4 x 1 1/4 x 1/2	0.30	1/2	1/2	25/32
1 1/4 x 1 1/4 x 3/8	0.34	23/32	23/32	29/32
1 1/4 x 1 x 1 1/4	0.43	13/16	11/32	13/16
1 1/4 x 1 x 1	0.47	25/32	7/8	29/32
1 1/4 x 1 x 3/4	0.35	21/32	25/32	7/8
1 1/4 x 1 x 1/2	0.30	1/2	5/8	29/32
1 1/4 x 3/4 x 1 1/4	0.42	13/16	11/8	13/16
1 1/4 x 3/4 x 1	0.45	25/32	11/32	29/32
1 1/4 x 3/4 x 3/4	0.37	21/32	15/16	7/8
1 1/4 x 3/4 x 1/2	0.30	1/2	3/4	29/32
1 1/4 x 1/2 x 1 1/4	0.41	13/16	17/32	13/16
1 1/2	0.61	31/32	31/32	29/32
1 1/2 x 1 1/2 x 2	1.11	125/32	125/32	13/32
1 1/2 x 1 1/2 x 1 1/4	0.62	29/32	29/32	11/16
1 1/2 x 1 1/2 x 1	0.55	11/16	11/16	7/8
1 1/2 x 1 1/2 x 3/4	0.45	11/16	11/16	11/32
1 1/2 x 1 1/2 x 1/2	0.40	1/2	1/2	11/32
1 1/2 x 1 1/4 x 1 1/2	0.62	11/32	13/16	29/32
1 1/2 x 1 1/4 x 1 1/4	0.62	31/32	13/32	31/32
1 1/2 x 1 1/4 x 1	0.51	25/32	1	11/32
1 1/2 x 1 1/4 x 3/4	0.49	11/16	13/16	11/32
1 1/2 x 1 1/4 x 1/2	0.41	1/2	25/32	11/32
1 1/2 x 1 x 1 1/2	0.59	11/32	111/32	29/32
1 1/2 x 1 x 1 1/4	0.63	29/32	11/8	11/16
1 1/2 x 1 x 1	0.54	25/32	11/16	11/32
1 1/2 x 1 x 3/4	0.44	11/16	31/32	15/16
1 1/2 x 1 x 1/2	0.39	1/2	25/32	11/32
1 1/2 x 3/4 x 1 1/2	0.62	11/32	17/16	11/16
1 1/2 x 3/4 x 1 1/4	0.58	29/32	111/32	11/16
1 1/2 x 3/4 x 1	0.54	25/32	11/4	11/32
1 1/2 x 3/4 x 3/4	0.47	11/16	13/32	29/32
1 1/2 x 3/4 x 1/2	0.39	1/2	29/32	31/32
1 1/2 x 1/2 x 1 1/2	0.62	11/32	113/32	31/32

Continues...

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		C	F	G
2	1.30	19/32	19/32	11/32
2 x 2 x 2 1/2	2.34	2	2	121/32
2 x 2 x 1 1/2	1.17	11/4	11/4	123/32
2 x 2 x 1 1/4	1.12	9/32	9/32	17/8
2 x 2 x 1	0.90	27/32	27/32	11/4
2 x 2 x 3/4	0.88	19/32	19/32	11/4
2 x 2 x 1/2	1.17	11/4	11/4	21/4
2 x 1 1/2 x 2	1.16	19/32	17/8	111/32
2 x 1 1/2 x 1 1/2	1.15	11/4	13/4	123/32
2 x 1 1/2 x 1 1/4	1.15	7/32	13/4	111/32
2 x 1 1/2 x 3/4	0.83	21/32	15/16	17/32
2 x 1 1/2 x 1/2	1.12	11/4	125/32	21/4
2 x 1 1/4 x 2	1.58	19/32	115/32	19/32
2 x 1 1/4 x 1 1/2	1.16	11/4	131/32	123/32
2 x 1 1/4 x 1 1/4	1.19	15/16	111/32	111/32
2 x 1 1/4 x 1	0.90	27/32	19/32	111/32
2 x 1 1/4 x 3/4	0.85	21/32	1	18/27
2 x 1 x 2	1.11	11/8	125/32	11/4
2 x 1 x 1	0.89	27/32	19/32	111/32
2 x 3/4 x 2	1.15	19/32	23/16	11/4
2 x 1/2 x 2	1.15	19/32	23/8	11/4
2 1/2	2.40	15/8	15/8	15/8
2 1/2 x 2 1/2 x 2	1.97	15/16	15/16	121/32
2 1/2 x 2 1/2 x 1 1/2	1.53	13/32	13/32	121/32
2 1/2 x 2 1/2 x 1 1/4	1.72	13/32	13/32	127/32
2 1/2 x 2 1/2 x 1	1.34	25/32	25/32	111/16
2 1/2 x 2 1/2 x 3/4	1.34	25/32	25/32	113/16
2 1/2 x 2 1/2 x 1/2	1.34	25/32	25/32	21/8
2 1/2 x 2 x 2 1/2	1.99	121/32	23/32	121/32
2 1/2 x 2 x 2	1.95	111/32	15/8	123/32
2 1/2 x 2 x 1 1/2	1.57	13/32	213/32	121/32
2 1/2 x 2 x 1 1/4	1.57	13/32	119/32	127/32
2 1/2 x 2 x 1	1.40	25/32	19/32	13/4
2 1/2 x 2 x 3/4	1.35	25/32	19/32	127/32
2 1/2 x 1 1/2 x 1 1/2	1.76	13/32	113/32	13/8
2 1/2 x 1 1/4 x 2 1/2	2.40	121/32	27/16	121/32
2 1/2 x 1 x 2 1/2	2.04	121/32	223/32	121/32
2 1/2 x 3/4 x 2 1/2	2.00	121/32	211/16	121/32

Continues...


NOTE: Tee sizes are read Run x Run x Outlet.

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		C	F	G
3	3.15	17/8	17/8	21/32
3 x 3 x 2 1/2	3.55	129/32	129/32	23/8
3 x 3 x 2	3.19	115/32	115/32	131/32
3 x 3 x 1 1/2	3.08	115/32	115/32	29/32
3 x 3 x 1 1/4	3.10	115/32	115/32	27/16
3 x 3 x 1	2.12	27/32	27/32	131/32
3 x 3 x 3/4	2.39	27/32	27/32	23/16
3 x 3 x 1/2	1.82	27/32	27/32	23/8
3 x 2 1/2 x 3	3.08	17/8	23/8	131/32
3 x 2 1/2 x 2 1/2	3.12	129/32	211/32	25/32
3 x 2 1/2 x 2	2.28	115/32	127/32	131/32
3 x 2 x 3	3.62	129/32	217/32	115/16
3 x 2 x 2 1/2	3.56	129/32	29/16	25/16
3 x 2 x 2	3.22	115/32	131/32	131/32
3 x 1 1/2 x 3	3.13	129/32	225/32	23/32
3 x 1 1/4 x 3	3.63	129/32	225/32	115/16
3 x 1 x 3	3.20	131/32	219/32	23/16
3 x 3/4 x 3	3.55	131/32	229/32	23/16
3 1/2	5.20	217/32	217/32	217/32
4	8.12	213/32	213/32	217/32
4 x 4 x 3	6.70	21/32	21/32	221/32
4 x 4 x 2 1/2	6.65	21/32	21/32	35/32
4 x 4 x 2	5.82	115/32	115/32	27/16
4 x 4 x 1 1/2	3.94	111/32	111/32	217/32
4 x 4 x 1 1/4	4.04	111/32	111/32	229/32
4 x 4 x 1	3.72	1	1	29/16
4 x 4 x 3/4	3.70	1	1	211/16
4 x 3 x 4	7.05	225/32	37/32	217/32
4 x 3 x 3	5.03	21/32	215/32	215/32
4 x 3 x 2 1/2	5.04	21/32	215/32	229/32
4 x 3 x 2	5.87	115/32	131/32	27/16
4 x 2 1/2 x 4	7.19	225/32	315/32	227/32
4 x 2 x 4	7.08	225/32	319/32	227/32

Continued on next page.

Consult price sheet for Made to Order items and for minimum order quantities.

**TEES** *continued*




**611**  
Tee C x C x C – Wrot continued

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		C	F	G
5	8.29	2 <sup>27</sup> / <sub>32</sub>	2 <sup>27</sup> / <sub>32</sub>	3 <sup>13</sup> / <sub>32</sub>
5 x 5 x 4	7.09	2 <sup>7</sup> / <sub>32</sub>	2 <sup>9</sup> / <sub>32</sub>	3 <sup>3</sup> / <sub>16</sub>
5 x 5 x 3	5.91	1 <sup>25</sup> / <sub>32</sub>	1 <sup>25</sup> / <sub>32</sub>	3 <sup>3</sup> / <sub>16</sub>
5 x 5 x 2 1/2	5.90	1 <sup>5</sup> / <sub>16</sub>	1 <sup>5</sup> / <sub>16</sub>	3 <sup>3</sup> / <sub>16</sub>
5 x 5 x 2	5.29	1 <sup>1</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>16</sub>	3 <sup>3</sup> / <sub>16</sub>
5 x 5 x 1 1/2	4.87	1 <sup>1</sup> / <sub>32</sub>	1 <sup>1</sup> / <sub>32</sub>	3 <sup>3</sup> / <sub>16</sub>
5 x 5 x 1 1/4	4.50	1 <sup>1</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>16</sub>	3 <sup>3</sup> / <sub>16</sub>
5 x 5 x 1	4.20	9/16	9/16	3 <sup>3</sup> / <sub>16</sub>
5 x 4 x 5	8.53	2 <sup>27</sup> / <sub>32</sub>	4 <sup>29</sup> / <sub>32</sub>	3 <sup>13</sup> / <sub>32</sub>
5 x 4 x 4	8.17	2 <sup>1</sup> / <sub>4</sub>	4 <sup>17</sup> / <sub>32</sub>	3 <sup>3</sup> / <sub>8</sub>
5 x 2 x 5	9.47	2 <sup>3</sup> / <sub>4</sub>	5 <sup>1</sup> / <sub>16</sub>	3 <sup>1</sup> / <sub>2</sub>
6	13.50	3 <sup>9</sup> / <sub>32</sub>	3 <sup>9</sup> / <sub>32</sub>	4 <sup>1</sup> / <sub>32</sub>
6 x 6 x 5	11.67	2 <sup>25</sup> / <sub>32</sub>	2 <sup>25</sup> / <sub>32</sub>	4 <sup>1</sup> / <sub>32</sub>
6 x 6 x 4	10.17	2 <sup>9</sup> / <sub>32</sub>	2 <sup>9</sup> / <sub>32</sub>	3 <sup>11</sup> / <sub>16</sub>
6 x 6 x 3	8.92	1 <sup>25</sup> / <sub>32</sub>	1 <sup>25</sup> / <sub>32</sub>	3 <sup>11</sup> / <sub>16</sub>
6 x 6 x 2 1/2	8.11	1 <sup>17</sup> / <sub>32</sub>	1 <sup>17</sup> / <sub>32</sub>	3 <sup>3</sup> / <sub>4</sub>
6 x 6 x 2	7.78	1 <sup>9</sup> / <sub>32</sub>	1 <sup>9</sup> / <sub>32</sub>	3 <sup>11</sup> / <sub>16</sub>
6 x 6 x 1 1/2	6.86	1	1	3 <sup>11</sup> / <sub>16</sub>
6 x 6 x 1 1/4	6.66	2 <sup>9</sup> / <sub>32</sub>	2 <sup>9</sup> / <sub>32</sub>	3 <sup>11</sup> / <sub>16</sub>
6 x 6 x 1	7.19	9/16	9/16	3 <sup>11</sup> / <sub>16</sub>
6 x 6 x 3/4	7.18	9/16	9/16	4 <sup>9</sup> / <sub>16</sub>
6 x 6 x 1/2	7.17	9/16	9/16	4 <sup>11</sup> / <sub>16</sub>
6 x 4 x 6	16.60	3 <sup>3</sup> / <sub>16</sub>	5 <sup>1</sup> / <sub>8</sub>	4 <sup>1</sup> / <sub>8</sub>
6 x 4 x 1 1/2	9.62	1 <sup>5</sup> / <sub>16</sub>	2 <sup>15</sup> / <sub>16</sub>	3 <sup>3</sup> / <sub>4</sub>
8	36.81	4 <sup>1</sup> / <sub>16</sub>	4 <sup>1</sup> / <sub>16</sub>	5 <sup>1</sup> / <sub>32</sub>
8 x 8 x 6	27.86	3 <sup>1</sup> / <sub>16</sub>	3 <sup>1</sup> / <sub>16</sub>	5 <sup>1</sup> / <sub>8</sub>
8 x 8 x 5	24.90	2 <sup>25</sup> / <sub>32</sub>	2 <sup>25</sup> / <sub>32</sub>	4 <sup>15</sup> / <sub>16</sub>
8 x 8 x 4	22.26	2 <sup>1</sup> / <sub>16</sub>	2 <sup>1</sup> / <sub>16</sub>	4 <sup>3</sup> / <sub>4</sub>
8 x 8 x 3	20.01	1 <sup>9</sup> / <sub>16</sub>	1 <sup>9</sup> / <sub>16</sub>	4 <sup>3</sup> / <sub>4</sub>
8 x 8 x 2 1/2	19.02	1 <sup>5</sup> / <sub>16</sub>	1 <sup>5</sup> / <sub>16</sub>	4 <sup>3</sup> / <sub>4</sub>
8 x 8 x 2	18.01	1 <sup>1</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>16</sub>	4 <sup>3</sup> / <sub>4</sub>

NOTE: Tee sizes are read Run x Run x Outlet.


**611-HE**  
Heat Exchanger Tee  
C x C x C – Wrot

Tube slips entirely through fitting on small end of run. Sizes same as listed under 611 where tee has one or more reductions on one end of run.



**711**  
Tee C x C x C – Cast


NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		C	F	G
1 1/4 x 1/2 x 1	0.48	3/4	3/4	7/8
1 1/4 x 1/2 x 1/2	0.50	9/16	5/8	1
1 1/2 x 1/2 x 1 1/4	0.70	7/8	3 <sup>1</sup> / <sub>32</sub>	1
2 x 2 x 3	3.11	1 <sup>21</sup> / <sub>32</sub>	1 <sup>21</sup> / <sub>32</sub>	1 <sup>5</sup> / <sub>16</sub>
2 x 1 x 1 1/2	1.23	1	1 <sup>1</sup> / <sub>4</sub>	1 <sup>1</sup> / <sub>4</sub>
2 x 3/4 x 3/4	0.84	2 <sup>1</sup> / <sub>32</sub>	7/8	1 <sup>1</sup> / <sub>4</sub>
2 1/2 x 2 1/2 x 3	2.98	1 <sup>3</sup> / <sub>4</sub>	1 <sup>3</sup> / <sub>4</sub>	1 <sup>17</sup> / <sub>32</sub>
2 1/2 x 1 1/2 x 2	2.02	1 <sup>1</sup> / <sub>4</sub>	1 <sup>15</sup> / <sub>32</sub>	1 <sup>1</sup> / <sub>2</sub>
2 1/2 x 1 1/2 x 1 1/2	1.76	1 <sup>3</sup> / <sub>32</sub>	1 <sup>13</sup> / <sub>32</sub>	1 <sup>3</sup> / <sub>8</sub>
2 1/2 x 1 1/2 x 2 1/2	2.46	1 <sup>1</sup> / <sub>2</sub>	2 <sup>7</sup> / <sub>32</sub>	1 <sup>1</sup> / <sub>2</sub>
3 x 3 x 4	6.96	2 <sup>11</sup> / <sub>32</sub>	2 <sup>11</sup> / <sub>32</sub>	1 <sup>23</sup> / <sub>32</sub>
3 x 2 1/2 x 1 1/2	2.53	1	1 <sup>3</sup> / <sub>32</sub>	1 <sup>3</sup> / <sub>4</sub>
3 x 2 x 1 1/2	2.62	1	1 <sup>1</sup> / <sub>4</sub>	1 <sup>3</sup> / <sub>4</sub>
4 x 4 x 6	16.47	3 <sup>7</sup> / <sub>32</sub>	3 <sup>7</sup> / <sub>32</sub>	2 <sup>9</sup> / <sub>32</sub>
4 x 2 x 2	4.64	1 <sup>1</sup> / <sub>4</sub>	1 <sup>3</sup> / <sub>4</sub>	2 <sup>1</sup> / <sub>4</sub>



**711-A**  
Supply and Return Tee  
C x C x C – Cast


NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES	
		C	J
1/2	0.17	1 <sup>3</sup> / <sub>16</sub>	1

Consult price sheet for Made to Order items and for minimum order quantities.



**611-2**  
Fitting Tee C x Ftg x C – Wrot


NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		B	C	F
1/2	0.07	1 <sup>1</sup> / <sub>32</sub>	3/8	7/16
3/4	0.15	1 <sup>15</sup> / <sub>32</sub>	1/2	1 <sup>7</sup> / <sub>32</sub>



**711-5**  
Drop Tee C x C x C – Cast


NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES	
		A	C
1/2	0.16	3/8	7/16

## TEES *continued*





712  
Tee C x C x F – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		E	F	G
3/8	0.11	1 <sup>1</sup> / <sub>16</sub>	7 <sup>7</sup> / <sub>16</sub>	7 <sup>7</sup> / <sub>16</sub>
1/2	0.14	1 <sup>3</sup> / <sub>16</sub>	7 <sup>7</sup> / <sub>16</sub>	7 <sup>7</sup> / <sub>16</sub>
3/4	0.33	1	2 <sup>1</sup> / <sub>32</sub>	2 <sup>1</sup> / <sub>32</sub>
1	0.54	1 <sup>1</sup> / <sub>4</sub>	7 <sup>7</sup> / <sub>8</sub>	7 <sup>7</sup> / <sub>8</sub>
1 1/2	1.08	1 <sup>5</sup> / <sub>8</sub>	1 <sup>1</sup> / <sub>8</sub>	1 <sup>1</sup> / <sub>8</sub>
2	1.74	1 <sup>7</sup> / <sub>8</sub>	1 <sup>3</sup> / <sub>8</sub>	1 <sup>3</sup> / <sub>8</sub>
1/2 x 1/2 x 1/4	0.16	1 <sup>3</sup> / <sub>16</sub>	1/2	1/2
1/2 x 1/2 x 3/8	0.15	1 <sup>3</sup> / <sub>16</sub>	1/2	1/2
1/2 x 1/2 x 3/4	0.23	1 <sup>5</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>16</sub>
3/4 x 3/4 x 3/8	0.23	7 <sup>7</sup> / <sub>8</sub>	1/2	1/2
3/4 x 3/4 x 1/2	0.24	5 <sup>7</sup> / <sub>64</sub>	1 <sup>7</sup> / <sub>32</sub>	1 <sup>7</sup> / <sub>32</sub>
1 1/4 x 1 1/4 x 1/2	0.49	1 <sup>1</sup> / <sub>4</sub>	9 <sup>9</sup> / <sub>16</sub>	9 <sup>9</sup> / <sub>16</sub>
1 1/4 x 1 1/4 x 3/4	0.55	1 <sup>5</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>16</sub>
1 1/4 x 1 1/4 x 1	0.66	1 <sup>7</sup> / <sub>16</sub>	7 <sup>7</sup> / <sub>8</sub>	7 <sup>7</sup> / <sub>8</sub>
1 x 1 x 1/2	0.34	1 <sup>1</sup> / <sub>8</sub>	9 <sup>9</sup> / <sub>16</sub>	9 <sup>9</sup> / <sub>16</sub>
1 x 1 x 3/4	0.42	1 <sup>3</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>16</sub>
1 1/2 x 1 1/2 x 1/2	0.62	1 <sup>3</sup> / <sub>8</sub>	9 <sup>9</sup> / <sub>16</sub>	9 <sup>9</sup> / <sub>16</sub>
1 1/2 x 1 1/2 x 3/4	0.70	1 <sup>7</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>16</sub>
1 1/2 x 1 1/2 x 1	0.79	1 <sup>1</sup> / <sub>2</sub>	1 <sup>3</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>16</sub>
2 x 2 x 1/2	0.97	1 <sup>5</sup> / <sub>8</sub>	1 <sup>7</sup> / <sub>32</sub>	1 <sup>7</sup> / <sub>32</sub>
2 x 2 x 3/4	1.10	1 <sup>11</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>16</sub>
2 x 2 x 1	1.23	1 <sup>3</sup> / <sub>4</sub>	1 <sup>3</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>16</sub>
1/4	0.08	1 <sup>3</sup> / <sub>16</sub>	9 <sup>9</sup> / <sub>32</sub>	9 <sup>9</sup> / <sub>32</sub>
1 1/4	0.76	1 <sup>7</sup> / <sub>16</sub>	1	1
3/8 x 3/8 x 1/4	0.12	1 <sup>1</sup> / <sub>16</sub>	7 <sup>7</sup> / <sub>16</sub>	7 <sup>7</sup> / <sub>16</sub>
3/4 x 1/2 x 3/4	0.28	1	2 <sup>1</sup> / <sub>32</sub>	1 <sup>1</sup> / <sub>16</sub>
3/4 x 3/4 x 1	0.40	1 <sup>1</sup> / <sub>8</sub>	7 <sup>7</sup> / <sub>8</sub>	7 <sup>7</sup> / <sub>8</sub>




712-5  
Drop Tee C x C x F – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		A	C	E
1/2	0.25	3 <sup>3</sup> / <sub>8</sub>	9 <sup>9</sup> / <sub>16</sub>	7 <sup>7</sup> / <sub>8</sub>
3/4	0.38	1/2	2 <sup>1</sup> / <sub>32</sub>	1



713  
Tee C x C x M – Cast



NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES	
		E	F
1/2	0.15	1 <sup>3</sup> / <sub>32</sub>	7 <sup>7</sup> / <sub>16</sub>
3/4	0.29	1 <sup>9</sup> / <sub>32</sub>	9 <sup>9</sup> / <sub>16</sub>



714  
Tee C x F x C – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		C	E	S
1/2	0.18	7 <sup>7</sup> / <sub>16</sub>	9 <sup>9</sup> / <sub>16</sub>	7 <sup>7</sup> / <sub>8</sub>
1/2 x 3/4 x 1/2	0.27	7 <sup>7</sup> / <sub>16</sub>	9 <sup>9</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>16</sub>
3/4	0.31	9 <sup>9</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>16</sub>	1
3/4 x 1/2 x 3/4	0.26	9 <sup>9</sup> / <sub>16</sub>	9 <sup>9</sup> / <sub>16</sub>	1 <sup>5</sup> / <sub>16</sub>
1	0.52	2 <sup>3</sup> / <sub>32</sub>	1 <sup>3</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>4</sub>
1 x 3/4 x 1	0.43	2 <sup>3</sup> / <sub>32</sub>	2 <sup>3</sup> / <sub>32</sub>	1 <sup>3</sup> / <sub>16</sub>
1 x 1/2 x 1	0.42	3 <sup>3</sup> / <sub>4</sub>	3 <sup>3</sup> / <sub>4</sub>	1 <sup>1</sup> / <sub>8</sub>
1 1/4	0.70	7 <sup>7</sup> / <sub>8</sub>	1	1 <sup>13</sup> / <sub>32</sub>
1 1/4 x 3/4 x 1 1/4	0.62	7 <sup>7</sup> / <sub>8</sub>	7 <sup>7</sup> / <sub>8</sub>	1 <sup>7</sup> / <sub>32</sub>
1 1/4 x 1/2 x 1 1/4	0.56	7 <sup>7</sup> / <sub>8</sub>	7 <sup>7</sup> / <sub>8</sub>	1 <sup>3</sup> / <sub>16</sub>
1 1/2	1.00	1	1 <sup>1</sup> / <sub>8</sub>	1 <sup>9</sup> / <sub>16</sub>
1 1/2 x 3/4 x 1 1/2	0.88	1	1	1 <sup>13</sup> / <sub>16</sub>
2	1.72	1 <sup>1</sup> / <sub>4</sub>	1 <sup>3</sup> / <sub>8</sub>	1 <sup>7</sup> / <sub>8</sub>
2 x 3/4 x 2	1.57	1 <sup>1</sup> / <sub>4</sub>	1 <sup>1</sup> / <sub>4</sub>	2
2 x 1/2 x 2	1.58	1 <sup>1</sup> / <sub>4</sub>	1 <sup>1</sup> / <sub>4</sub>	2

## TRAPS





698  
Suction Line P-Trap  
C x C – Wrot

A major application of this fitting is on the suction line of a refrigeration compressor. The line is looped, by use of the Suction Line P-Trap, to the floor prior to being run vertically upwards to prevent the drainage of oil back to the compressor during shut down periods. Additional P-Traps are used for each 20' or riser pipe. This prevents high velocity build-up as the oil or liquid begins to return to the compressor during this shut down period.

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES			
		C	D	J	K
1/2	0.36	5 <sup>3</sup> / <sub>8</sub>	3	3	6
5/8	0.45	5 <sup>3</sup> / <sub>8</sub>	2 <sup>7</sup> / <sub>8</sub>	3	6
3/4	0.58	5 <sup>3</sup> / <sub>8</sub>	2 <sup>3</sup> / <sub>4</sub>	3	6
1	0.92	5 <sup>1</sup> / <sub>4</sub>	2 <sup>21</sup> / <sub>32</sub>	3	6
1 1/4	1.16	5 <sup>3</sup> / <sub>8</sub>	2 <sup>7</sup> / <sub>8</sub>	3 <sup>3</sup> / <sub>4</sub>	6 <sup>1</sup> / <sub>8</sub>
1 1/2	2.32	7 <sup>5</sup> / <sub>8</sub>	3 <sup>5</sup> / <sub>8</sub>	5	9
2	3.93	8	3 <sup>5</sup> / <sub>8</sub>	6	9 <sup>1</sup> / <sub>16</sub>


Consult price sheet for Made to Order items and for minimum order quantities.

## UNIONS



633-W  
Union C x C – Wrot



NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1/8	0.10	5/8
1/4	0.15	11/16
3/8	0.22	7/16
1/2	0.31	13/32
3/4	0.33	3/8
1	0.54	1/2



733  
Union C x C – Cast


NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1/4	0.10	11/16
3/8	0.15	7/16
1/2	0.22	13/32
5/8	0.31	21/32
3/4	0.31	3/8
1	0.54	1/2
1 1/4	0.76	1/2
1 1/2	1.04	23/32
2	1.77	1/2
2 1/2	3.25	1
3	4.75	1 5/32

Consult price sheet for Made to Order items and for minimum order quantities.




733-2  
Fitting Union Ftg x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1/2	0.23	1 9/32
3/4	0.35	1 5/8
1	0.55	1 27/32



733-3  
Fitting Union C x F – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1/4	0.14	1 5/32
3/8	0.19	1 3/32
1/2	0.26	1 1/8
3/4	0.37	1 5/16
1	0.61	1 7/16
1 1/4	0.98	1 19/32
1 1/2	1.21	1 13/16
2	1.90	2 5/32



733-4  
Union C x M – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1/4	0.13	1 1/2
3/8	0.20	1 5/8
1/2	0.28	1 11/16
1/2 x 3/4	0.35	2 1/16
3/4	0.43	1 29/32
1	0.68	2 1/8
1 1/4	0.95	2 5/32
1 1/2	1.35	2 13/32
2	2.17	2 25/32
2 1/2	4.13	3 13/32

## VENTURI





621  
Venturi Insert – Wrot

Converts any tee into a special purpose venturi or scoop tee


NOM. SIZE	APPROX. NET WT./LBS.
1/2	0.01
3/4	0.02
1	0.03
1 1/4	0.04

## Y's



748  
90° Y C x C x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. B INCHES
1/2	0.11	7/32	7/16
3/4	0.25	7/16	5/8
1	0.61	1/2	13/16



749  
45° Y C x C x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. B INCHES
1/2	0.15	1 3/32	7/8
3/4	0.30	1 17/32	1 7/32
1	0.55	1 13/16	1 15/32
1 1/4	0.81	2 1/4	1 7/8
1 1/2	1.14	2 5/8	2 1/8
2	2.17	3 5/16	2 3/4



## Cast Copper Alloy Flared Fittings

**100 Series – Heavy Flared**  
**500 Series – Flared**


Adapters .....	23
Couplings .....	23
Elbows .....	23
Nuts .....	24
Tees .....	24



The manufacturing plants at Stuarts Draft, VA, Nacogdoches, TX and Reynosa, Mexico manufacture products under a Quality Management System conforming to the current revision of ISO-9001 International Standards




## ADAPTERS




104  
Heavy Flared Adapter  
FL x M – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. L INCHES
3/4	0.60	2 <sup>1</sup> / <sub>2</sub>
1	1.24	3 <sup>1</sup> / <sub>4</sub>



503  
Flared Adapter FL x F – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1/2	0.36	1 <sup>7</sup> / <sub>8</sub>
3/4	0.48	2 <sup>1</sup> / <sub>32</sub>
1	1.03	2 <sup>3</sup> / <sub>4</sub>
1 1/2	1.99	3 <sup>7</sup> / <sub>32</sub>
2	3.22	3 <sup>9</sup> / <sub>16</sub>




504  
Flared Adapter FL x M – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1/2	0.29	1 <sup>32</sup> / <sub>32</sub>
3/4	0.58	2 <sup>11</sup> / <sub>16</sub>
1	0.88	3 <sup>3</sup> / <sub>16</sub>
1 1/2	1.89	3 <sup>3</sup> / <sub>4</sub>
2	2.95	4 <sup>15</sup> / <sub>16</sub>


Consult price sheet for Made to Order items and for minimum order quantities.

## COUPLINGS



101  
Heavy Flared Coupling  
FL x FL – Cast


NOM. SIZE	APPROX. NET WT./LBS.	DIM. L INCHES
3/4	0.98	3 <sup>13</sup> / <sub>16</sub>
1	1.70	5 <sup>5</sup> / <sub>16</sub>



501  
Flared Coupling FL x FL – Cast


NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1/2	0.45	2 <sup>3</sup> / <sub>8</sub>
3/4	0.60	2 <sup>1</sup> / <sub>2</sub>
1	1.24	3 <sup>1</sup> / <sub>4</sub>
1 1/4	2.18	3 <sup>1</sup> / <sub>2</sub>
1 1/2	2.65	3 <sup>23</sup> / <sub>32</sub>
2	4.03	4 <sup>1</sup> / <sub>4</sub>

## ELBOWS




507  
Flared 90° Elbow FL x FL – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1/2	0.54	1 <sup>5</sup> / <sub>8</sub>
3/4	0.77	1 <sup>31</sup> / <sub>32</sub>
1	1.60	2 <sup>9</sup> / <sub>16</sub>
2	5.39	3 <sup>7</sup> / <sub>8</sub>



507-3  
Flared 90° Elbow FL x F – Cast


NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES	DIM. E INCHES
1/2	0.49	1 <sup>5</sup> / <sub>8</sub>	1 <sup>1</sup> / <sub>2</sub>
3/4	0.69	1 <sup>15</sup> / <sub>16</sub>	1 <sup>5</sup> / <sub>8</sub>
1	1.43	2 <sup>9</sup> / <sub>16</sub>	2 <sup>1</sup> / <sub>4</sub>



507-4  
Flared 90° Elbow FL x M – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES	DIM. E INCHES
1/2	0.34	1 <sup>11</sup> / <sub>16</sub>	1 <sup>13</sup> / <sub>32</sub>
3/4	0.55	1 <sup>31</sup> / <sub>32</sub>	1 <sup>19</sup> / <sub>32</sub>
1	1.34	2 <sup>3</sup> / <sub>32</sub>	2
1 1/2	2.80	3 <sup>5</sup> / <sub>16</sub>	2 <sup>1</sup> / <sub>2</sub>


## NUTS



500  
Tube Nut – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES	DIM. L INCHES
3/4	0.20	1 <sup>1</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>2</sub>
1	0.31	1 <sup>3</sup> / <sub>8</sub>	1 <sup>7</sup> / <sub>8</sub>

## TEES



511  
Flared Tee FL x FL x FL – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		B	D	K
1/2	0.67	1 <sup>5</sup> / <sub>8</sub>	1 <sup>5</sup> / <sub>8</sub>	1 <sup>5</sup> / <sub>8</sub>
3/4	1.09	2	2	2
1	2.08	2 <sup>5</sup> / <sub>8</sub>	2 <sup>5</sup> / <sub>8</sub>	2 <sup>5</sup> / <sub>8</sub>

Consult price sheet for Made to Order items and for minimum order quantities.

## Copper Insert Fittings for Polybutylene

Couplings .....	26
Crimp Rings .....	26
Elbows .....	26
Faucet Connectors .....	26
Tees .....	26



The manufacturing plants at Stuarts Draft, VA, Nacogdoches, TX and Reynosa, Mexico manufacture products under a Quality Management System conforming to the current revision of ISO-9001 International Standards

## COUPLINGS



PB600  
Coupling – Barb x Barb

NOM. SIZE	APPROX. NET WT./LBS.
1/2	0.04
3/4	0.06


## ELBOWS



PB607  
90° Elbow – Barb x Barb

NOM. SIZE	APPROX. NET WT./LBS.
1/2	0.04
3/4	0.06

## FAUCET CONNECTORS



PB600-FA  
Straight Faucet Connector – Barb x Swivel FIPS

NOM. SIZE	APPROX. NET WT./LBS.
1/2 without nut & washer	0.03

Consult price sheet for Made to Order items and for minimum order quantities.

## FAUCET CONNECTORS



PB607-FA  
90° Elbow Faucet Connector – Barb x Swivel FIPS

NOM. SIZE	APPROX. NET WT./LBS.
1/2 without nut & washer	0.04

## TEES



PB611  
Tee – Barb x Barb x Barb

NOM. SIZE	APPROX. NET WT./LBS.
1/2	0.05
1/2 x 1/2 x 3/4	0.10
3/4	0.10
3/4 x 3/4 x 1/2	0.08
3/4 x 1/2 x 3/4	0.10
3/4 x 1/2 x 1/2	0.08

## CRIMP RINGS



PB198  
Crimp Ring – Copper

NOM. SIZE	APPROX. NET WT./LBS.
1/2	0.01
3/4	0.02


## Wrot and Cast DWV Fittings

Adapters .....	28-30
Bushings .....	30
Cleanouts .....	30
Closet Flanges .....	31
Couplings .....	31
Elbows .....	32-33
Plugs .....	33
Tees .....	34
Test Caps & Tees .....	34-35
T-Y's .....	35
Y's .....	35
Traps .....	36-37
Return Bends .....	37




The manufacturing plants at Stuarts Draft, VA, Nacogdoches, TX and Reynosa, Mexico manufacture products under a Quality Management System conforming to the current revision of ISO-9001 International Standards

## ADAPTERS – SLIP JOINT




801-2-7  
DWV Fitting Trap Adapter  
Ftg x SJ – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1 1/4 x 1 1/4 O.D.	0.25	1 <sup>19</sup> / <sub>32</sub>



901-2-7  
DWV Fitting Trap Adapter  
Ftg x SJ – Wrot


NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1 1/2 x 1 1/2 O.D.	0.29	1 <sup>7</sup> / <sub>16</sub>
1 1/2 x 1 1/4 O.D.	0.24	1 <sup>7</sup> / <sub>16</sub>



901-7  
DWV Trap Adapter  
C x SJ – Wrot


NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1 1/4 x 1 1/4 O.D.	0.21	2 <sup>1</sup> / <sub>32</sub>
1 1/2 x 1 1/2 O.D.	0.27	3/4
1 1/2 x 1 1/4 O.D.	0.24	7/8

Consult price sheet for Made to Order items and for minimum order quantities.



903-7  
DWV Trap Adapter  
F x SJ – Wrot


NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1 1/4 x 1 1/4 O.D.	0.32	1 <sup>7</sup> / <sub>16</sub>
1 1/2 x 1 1/2 O.D.	0.42	1 <sup>7</sup> / <sub>16</sub>
1 1/2 x 1 1/4 O.D.	0.43	1 <sup>19</sup> / <sub>32</sub>



904-7  
DWV Trap Adapter  
M x SJ – Wrot


NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1 1/4 x 1 1/4 O.D.	0.41	1 <sup>3</sup> / <sub>4</sub>
1 1/2 x 1 1/2 O.D.	0.51	1 <sup>25</sup> / <sub>32</sub>
1 1/2 x 1 1/4 O.D.	0.49	1 <sup>29</sup> / <sub>32</sub>

## ADAPTERS – SOIL PIPE




805  
DWV Soil Pipe Adapter  
C x Spigot – Cast  
Joins copper tube to cast iron soil pipes.

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1 1/4 x 2	0.93	3 <sup>9</sup> / <sub>32</sub>
2 x 4	2.52	3 <sup>7</sup> / <sub>8</sub>
3	1.56	2 <sup>3</sup> / <sub>4</sub>
3 x 4	2.78	3 <sup>13</sup> / <sub>16</sub>
4	2.23	3



905  
DWV Soil Pipe Adapter  
C x Spigot – Wrot  
Joins copper tube to cast iron soil pipes.


NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1 1/2 x 2	0.60	3 <sup>7</sup> / <sub>16</sub>
2	0.44	2 <sup>9</sup> / <sub>16</sub>



805-N  
DWV No Hub Soil Pipe Adapter  
C x No Hub – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1 1/2 x 2	0.42	1 <sup>7</sup> / <sub>32</sub>
2	0.40	1 <sup>3</sup> / <sub>16</sub>
3	0.75	1 <sup>3</sup> / <sub>16</sub>
4	1.23	1 <sup>7</sup> / <sub>32</sub>


**ADAPTERS – SPECIAL LEAD**



801-T  
DWV Trap Adapter  
C x O.D. Tube – Cast


NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES
1 1/4 x 1 1/4 O.D.	0.21	1/8
1 1/2 x 1 1/2 O.D.	0.22	7/32
1 1/2 x 1 1/4 O.D.	0.20	9/32

**ADAPTERS – THREADED**



802  
DWV Adapter  
C x M – Cast


NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES	DIM. C INCHES
1 1/4	0.23	15/16	7/16
1 1/4 x 1 1/2	0.41	1	1/2
1 1/2	0.25	1	7/16
2	0.33	1 1/16	7/16
3	0.92	1 1/2	3/4



802-C  
DWV Flush Adapter  
C x M – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES	DIM. C INCHES
1 1/4	0.16	15/16	7/16
1 1/2	0.20	15/16	9/16
2	0.23	1 1/16	5/8


**ADAPTERS – THREADED *continued***



802-F  
DWV Threaded Piece  
C x M – Cast


Makes slip joint connection when soldered to the end of tube and slip joint nut and washer added.

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1 1/4	0.05	3/8
1 1/2	0.05	3/8
2	0.05	3/8




803  
DWV Adapter  
C x F – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
3	1.45	1 13/32
4	2.31	1 17/32




903  
DWV Adapter  
C x F – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1 1/4	0.19	27/32
1 1/2	0.25	29/32
2	0.41	1




803-2  
DWV Fitting Adapter  
Ftg x F – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1 1/2	0.39	1 15/32
2	0.56	1 19/32
3	1.44	2 7/32



903-2  
DWV Fitting Adapter  
Ftg x F – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1 1/4	0.19	1 17/32




804  
DWV Adapter  
C x M – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1 1/2	0.34	1 3/64
1 1/2 x 2	0.55	1 5/16
1 1/2 x 1 1/4	0.31	27/32
2	0.43	7/8
2 x 1 1/2	0.52	1 5/16
3	1.35	1 25/32
4	2.59	2 1/32

Consult price sheet for Made to Order items and for minimum order quantities.




## ADAPTERS – THREADED *continued*



904  
DWV Adapter  
C x M – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1 1/4	0.30	1 <sup>3</sup> / <sub>32</sub>
1 1/4 x 1 1/2	0.37	1 <sup>3</sup> / <sub>16</sub>



804-T  
DWV Trap Adapter  
O.D. Tube x M – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1 1/4 O.D. x 1 1/2	0.44	1 <sup>9</sup> / <sub>32</sub>




804-2  
DWV Fitting Adapter  
Ftg x M – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1 1/2	0.50	1 <sup>15</sup> / <sub>16</sub>
2	0.71	2 <sup>1</sup> / <sub>32</sub>


Consult price sheet for Made to Order items and for minimum order quantities.

## BUSHINGS




801-2  
DWV External Bushing  
Ftg x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
3 x 2	0.61	1 <sup>11</sup> / <sub>32</sub>
3 x 1 1/2	0.60	1 <sup>5</sup> / <sub>16</sub>
4 x 3	1.12	1 <sup>21</sup> / <sub>32</sub>
4 x 2	1.16	1 <sup>3</sup> / <sub>4</sub>



901-2  
DWV External Bushing  
Ftg x C – Wrot


NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1 1/2 x 1 1/4	0.13	1
2 x 1 1/2	0.19	1 <sup>7</sup> / <sub>32</sub>
2 x 1 1/4	0.19	1 <sup>3</sup> / <sub>8</sub>



901-2-F  
DWV Fitting Flush Bushing  
Ftg x C – Wrot


NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES	DIM. C INCHES
2 x 1 1/2	0.37	1 <sup>3</sup> / <sub>16</sub>	1/8

## CLEANOUTS



816  
DWV Fitting Cleanout  
Ftg x Cleanout w/Plug – Cast



NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1 1/4	0.49	2 <sup>5</sup> / <sub>32</sub>
1 1/2	0.60	2 <sup>1</sup> / <sub>4</sub>
2	0.87	2 <sup>3</sup> / <sub>8</sub>
3	2.37	3 <sup>3</sup> / <sub>32</sub>
4	3.99	3 <sup>5</sup> / <sub>8</sub>



816-S  
DWV Flush Fitting Cleanout  
Ftg x Cleanout w/Plug – Cast


NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1 1/4 x 3/4	0.20	1 <sup>5</sup> / <sub>32</sub>
1 1/2 x 1	0.29	1 <sup>1</sup> / <sub>16</sub>
2 x 1 1/2	0.42	1 <sup>7</sup> / <sub>32</sub>
3 x 2 1/2	0.96	1 <sup>13</sup> / <sub>16</sub>
4 x 3	2.25	2 <sup>1</sup> / <sub>8</sub>

## CLOSET FLANGES




851  
DWV Closet Flange  
C – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		B	F	W
4	1.45	5/8	7	6
4 x 3	2.18	1 <sup>11</sup> / <sub>16</sub>	7	6



951  
DWV Closet Flange  
C – Wrot


NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		B	F	W
4 x 3	0.84	1 <sup>11</sup> / <sub>16</sub>	6 <sup>3</sup> / <sub>4</sub>	6



851-C  
DWV Closet Flange  
C – Cast


NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES			
		B	C	F	W
4 x 3	1.31	1 <sup>1</sup> / <sub>16</sub>	1/2	6 <sup>7</sup> / <sub>8</sub>	6

## COUPLINGS




801  
DWV Coupling  
C x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
3 x 2	0.70	1 <sup>11</sup> / <sub>16</sub>
3 x 1 1/2	0.68	1 <sup>5</sup> / <sub>16</sub>
4 x 3	0.98	9/32
4 x 2	1.34	1 <sup>1</sup> / <sub>4</sub>



901  
DWV Coupling  
C x C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES
1 1/4	0.07	3/32
1 1/2	0.09	3/32
1 1/2 x 1 1/4	0.13	5/16
2	0.14	3/32
2 x 1 1/2	0.19	1 <sup>5</sup> / <sub>32</sub>
3	0.45	3/32
4	0.57	1/8




901-RP  
DWV Repair Coupling (No Stop)  
C x C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
1 1/2	0.09	1 <sup>13</sup> / <sub>32</sub>
2	0.14	1 <sup>17</sup> / <sub>32</sub>
3	0.42	1 <sup>29</sup> / <sub>32</sub>
4	0.57	2 <sup>13</sup> / <sub>32</sub>


Consult price sheet for Made to Order items and for minimum order quantities.

## ELBOWS




806  
DWV 45° Elbow  
C x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES
4	2.47	1 <sup>17</sup> / <sub>32</sub>




906  
DWV 45° Elbow  
C x C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES
1 1/4	0.13	1/2
1 1/2	0.21	9/16
2	0.38	13/16
3	0.78	13/16




806-2  
DWV 45° Fitting Elbow  
Ftg x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES	DIM. C INCHES
4	2.81	2 <sup>19</sup> / <sub>32</sub>	1 <sup>17</sup> / <sub>32</sub>




906-2  
DWV 45° Fitting Elbow  
Ftg x C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES	DIM. C INCHES
1 1/4	0.13	1 <sup>3</sup> / <sub>16</sub>	1/2
1 1/2	0.21	1 <sup>1</sup> / <sub>4</sub>	9/16
2	0.39	1 <sup>5</sup> / <sub>8</sub>	13/16
3	0.84	1 <sup>7</sup> / <sub>8</sub>	1 <sup>3</sup> / <sub>8</sub>




807  
DWV 90° Elbow  
C x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES	DIM. D INCHES
1 1/2 x 1 1/4	0.43	1 <sup>1</sup> / <sub>4</sub>	1 <sup>3</sup> / <sub>16</sub>
2 x 1 1/2	0.71	1 <sup>11</sup> / <sub>16</sub>	1 <sup>7</sup> / <sub>16</sub>
3	2.30	2 <sup>7</sup> / <sub>8</sub>	2 <sup>7</sup> / <sub>8</sub>
4	3.92	3 <sup>25</sup> / <sub>32</sub>	3 <sup>25</sup> / <sub>32</sub>




907  
DWV 90° Elbow  
C x C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES	DIM. D INCHES
1 1/4	0.18	1 <sup>3</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>16</sub>
1 1/2	0.32	1 <sup>7</sup> / <sub>16</sub>	1 <sup>7</sup> / <sub>16</sub>
2	0.58	1 <sup>15</sup> / <sub>16</sub>	1 <sup>15</sup> / <sub>16</sub>
3	1.20	2 <sup>11</sup> / <sub>16</sub>	2 <sup>11</sup> / <sub>16</sub>




907-LT  
DWV 90° Long Radius Elbow  
C x C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES
1 1/2	0.41	2 <sup>5</sup> / <sub>16</sub>
2	0.62	2 <sup>3</sup> / <sub>4</sub>



807-2  
DWV 90° Fitting Elbow  
Ftg x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES	DIM. C INCHES
4	3.84	4 <sup>13</sup> / <sub>16</sub>	3 <sup>25</sup> / <sub>32</sub>




907-2  
DWV 90° Fitting Elbow  
Ftg x C – Wrot

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES	DIM. C INCHES
1 1/4	0.19	1 <sup>7</sup> / <sub>8</sub>	1 <sup>3</sup> / <sub>16</sub>
1 1/2	0.33	2 <sup>3</sup> / <sub>16</sub>	1 <sup>7</sup> / <sub>16</sub>
2	0.59	2 <sup>11</sup> / <sub>16</sub>	1 <sup>7</sup> / <sub>8</sub>
3	1.21	3 <sup>11</sup> / <sub>16</sub>	2 <sup>11</sup> / <sub>16</sub>


Consult price sheet for Made to Order items and for minimum order quantities.

**ELBOWS** *continued*




807-3  
DWV 90° Elbow  
C x F – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES	DIM. E INCHES
1 1/2	0.72	1 <sup>13</sup> / <sub>32</sub>	2 <sup>1</sup> / <sub>8</sub>
2	1.15	1 <sup>7</sup> / <sub>8</sub>	2 <sup>11</sup> / <sub>16</sub>




807-4  
DWV 90° Elbow  
C x M – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES	DIM. E INCHES
1 1/2	0.66	1 <sup>13</sup> / <sub>32</sub>	2 <sup>3</sup> / <sub>32</sub>




807-9  
DWV 90° Elbow w/Side Inlet  
C x C x C – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		C	C <sub>1</sub>	D
3 x 3 x 2	2.55	2 <sup>7</sup> / <sub>8</sub>	1 <sup>5</sup> / <sub>8</sub>	2 <sup>7</sup> / <sub>8</sub>




837  
DWV 90° Double Elbow  
C x C x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES	DIM. G INCHES
1 1/2	0.77	1 <sup>13</sup> / <sub>32</sub>	1 <sup>13</sup> / <sub>32</sub>
2	1.31	1 <sup>7</sup> / <sub>8</sub>	1 <sup>7</sup> / <sub>8</sub>
2 x 1 1/2 x 1 1/2	0.97	1 <sup>5</sup> / <sub>8</sub>	1 <sup>1</sup> / <sub>2</sub>




808  
DWV 22<sup>1</sup>/<sub>2</sub>° Elbow  
C x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES
1 1/4	0.22	3 <sup>3</sup> / <sub>16</sub>
1 1/2	0.28	1 <sup>1</sup> / <sub>4</sub>
2	0.48	1 <sup>11</sup> / <sub>32</sub>
3	0.99	1 <sup>7</sup> / <sub>32</sub>




809  
DWV 11<sup>1</sup>/<sub>4</sub>° Elbow  
C x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES
1 1/2	0.22	5 <sup>5</sup> / <sub>32</sub>
2	0.38	3 <sup>3</sup> / <sub>16</sub>



960  
DWV 60° Elbow  
C x C – Wrot


NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES
1 1/2	0.24	1 <sup>3</sup> / <sub>16</sub>
2	0.44	1 <sup>1</sup> / <sub>8</sub>
3	0.95	1 <sup>7</sup> / <sub>8</sub>



861-LH  
DWV 90° Elbow  
w/Low Heel Inlet  
C x C x C – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. C INCHES	DIM. E INCHES
3 x 3 x 2	2.43	2 <sup>7</sup> / <sub>8</sub>	1 <sup>9</sup> / <sub>32</sub>

**PLUGS**




818 A.S.A.  
DWV Plug  
M – Cast

NOM. SIZE	APPROX. NET WT./LBS.	DIM. B INCHES
3/4	0.08	2 <sup>3</sup> / <sub>32</sub>
1	0.12	2 <sup>9</sup> / <sub>32</sub>
1 1/4	0.19	3 <sup>1</sup> / <sub>32</sub>
1 1/2	0.21	1 <sup>3</sup> / <sub>32</sub>
2	0.34	1 <sup>5</sup> / <sub>16</sub>


Consult price sheet for Made to Order items and for minimum order quantities.

## TEES




811  
DWV Tee  
C x C x C – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		C	F	G
3	2.84	2 <sup>53</sup> / <sub>64</sub>	1 <sup>25</sup> / <sub>64</sub>	2 <sup>53</sup> / <sub>64</sub>
3 x 3 x 2	1.82	2 <sup>3</sup> / <sub>8</sub>	1 <sup>1</sup> / <sub>8</sub>	1 <sup>7</sup> / <sub>8</sub>
3 x 3 x 1 1/2	1.58	2 <sup>5</sup> / <sub>32</sub>	1 <sup>5</sup> / <sub>16</sub>	1 <sup>7</sup> / <sub>16</sub>
4	4.92	3 <sup>13</sup> / <sub>16</sub>	2	3 <sup>13</sup> / <sub>16</sub>
4 x 4 x 3	3.49	3 <sup>11</sup> / <sub>32</sub>	1 <sup>19</sup> / <sub>32</sub>	2 <sup>7</sup> / <sub>8</sub>
4 x 4 x 2	2.91	2 <sup>7</sup> / <sub>8</sub>	1 <sup>5</sup> / <sub>32</sub>	1 <sup>13</sup> / <sub>32</sub>




911  
DWV Tee  
C x C x C – Wrot

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		C	F	G
1 1/4	0.32	1 <sup>1</sup> / <sub>8</sub>	1 <sup>3</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>8</sub>
1 1/2	0.49	1 <sup>13</sup> / <sub>32</sub>	2 <sup>9</sup> / <sub>32</sub>	1 <sup>13</sup> / <sub>32</sub>
1 1/2 x 1 1/2 x 1 1/4	1.58	2 <sup>5</sup> / <sub>32</sub>	1 <sup>5</sup> / <sub>16</sub>	1 <sup>7</sup> / <sub>16</sub>
2	0.78	1 <sup>27</sup> / <sub>32</sub>	1 <sup>1</sup> / <sub>8</sub>	1 <sup>7</sup> / <sub>8</sub>
2 x 2 x 1 1/2	0.73	1 <sup>5</sup> / <sub>8</sub>	1 <sup>5</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>8</sub>
2 x 2 x 1 1/4	0.51	1 <sup>1</sup> / <sub>2</sub>	1 <sup>3</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>8</sub>
2 x 1 1/2 x 2	0.80	1 <sup>27</sup> / <sub>32</sub>	1 <sup>25</sup> / <sub>32</sub>	1 <sup>13</sup> / <sub>16</sub>
2 x 1 1/2 x 1 1/2	0.73	1 <sup>5</sup> / <sub>8</sub>	1 <sup>1</sup> / <sub>4</sub>	1 <sup>3</sup> / <sub>8</sub>




811-14  
DWV Tee  
C x C x F – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		B	F	G
1 1/2	0.88	2 <sup>3</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>16</sub>	1 <sup>13</sup> / <sub>32</sub>
2	1.57	2 <sup>23</sup> / <sub>32</sub>	1 <sup>1</sup> / <sub>16</sub>	1 <sup>7</sup> / <sub>8</sub>
2 x 2 x 1 1/2	1.17	2 <sup>7</sup> / <sub>16</sub>	7 <sup>7</sup> / <sub>8</sub>	1 <sup>7</sup> / <sub>16</sub>




811-15  
DWV Tee  
C x F x F – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		B	E	G
1 1/4	0.73	1 <sup>25</sup> / <sub>32</sub>	1 <sup>1</sup> / <sub>2</sub>	1 <sup>5</sup> / <sub>32</sub>



835  
DWV Double Tee  
C x C x C x C – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		C	F	G
1 1/4	0.65	1 <sup>5</sup> / <sub>32</sub>	3 <sup>3</sup> / <sub>4</sub>	1 <sup>5</sup> / <sub>32</sub>
1 1/2	0.85	1 <sup>13</sup> / <sub>32</sub>	1 <sup>3</sup> / <sub>16</sub>	1 <sup>13</sup> / <sub>16</sub>
1 1/2 x 1 1/2 x 1 1/4 x 1 1/4	0.72	1 <sup>9</sup> / <sub>32</sub>	3 <sup>3</sup> / <sub>4</sub>	1 <sup>5</sup> / <sub>32</sub>
2	1.38	1 <sup>7</sup> / <sub>8</sub>	1 <sup>1</sup> / <sub>16</sub>	1 <sup>7</sup> / <sub>8</sub>
2 x 2 x 1 1/2 x 1 1/2	0.99	1 <sup>21</sup> / <sub>32</sub>	7 <sup>7</sup> / <sub>8</sub>	1 <sup>7</sup> / <sub>16</sub>
2 x 2 x 1 1/4 x 1 1/4	0.93	1 <sup>17</sup> / <sub>32</sub>	2 <sup>5</sup> / <sub>32</sub>	1 <sup>5</sup> / <sub>32</sub>
2 x 1 1/2 x 1 1/2 x 1 1/2	0.94	1 <sup>21</sup> / <sub>32</sub>	2 <sup>5</sup> / <sub>32</sub>	1 <sup>7</sup> / <sub>16</sub>
3 x 3 x 2 x 2	2.36	2 <sup>3</sup> / <sub>8</sub>	1 <sup>1</sup> / <sub>8</sub>	1 <sup>7</sup> / <sub>8</sub>
3 x 3 x 1 1/2 x 1 1/2	1.51	2 <sup>5</sup> / <sub>32</sub>	3 <sup>1</sup> / <sub>32</sub>	1 <sup>15</sup> / <sub>32</sub>



835-B  
DWV Double LT Tee  
C x C x C x C – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES			
		C	D	L	M
2 x 1 1/2 x 1 1/2 x 1 1/2	1.73	2 <sup>3</sup> / <sub>8</sub>	3 <sup>3</sup> / <sub>16</sub>	3 <sup>21</sup> / <sub>32</sub>	3 <sup>3</sup> / <sub>32</sub>

## TEST CAPS




917-B  
Test Caps – Copper  
C – Wrot

NOM. SIZE	APPROX. NET WT. LBS.	DIM. B INCHES
1/2	0.01	3 <sup>3</sup> / <sub>16</sub>
3/4	0.01	3 <sup>3</sup> / <sub>16</sub>
1	0.01	1 <sup>1</sup> / <sub>8</sub>
1 1/4	0.01	1 <sup>1</sup> / <sub>4</sub>
1 1/2	0.01	1 <sup>1</sup> / <sub>4</sub>
2	0.02	1 <sup>1</sup> / <sub>4</sub>
3	0.03	1 <sup>1</sup> / <sub>4</sub>
4	0.05	5 <sup>1</sup> / <sub>16</sub>

Consult price sheet for Made to Order items and for minimum order quantities.


## TEST TEES



814  
DWV Test Tee  
C x C x Cleanout w/Plug – Cast


NOM. SIZE	APPROX. NET WT./LBS.	DIM. E INCHES	DIM. F INCHES
1 1/2	1.00	2 <sup>1</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>8</sub>
2	1.35	2 <sup>11</sup> / <sub>32</sub>	1 <sup>3</sup> / <sub>8</sub>
3	3.78	3 <sup>7</sup> / <sub>16</sub>	1 <sup>15</sup> / <sub>16</sub>

## T-Y's



812  
DWV Long Turn T-Y  
C x C x C – Cast


NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES			
		C	D	J	K
§ 1 1/4	0.93	2 <sup>27</sup> / <sub>32</sub>	1 <sup>27</sup> / <sub>32</sub>	2 <sup>3</sup> / <sub>4</sub>	1 <sup>3</sup> / <sub>32</sub>
1 1/2	0.87	3 <sup>5</sup> / <sub>16</sub>	2 <sup>1</sup> / <sub>8</sub>	3 <sup>5</sup> / <sub>32</sub>	7 <sup>1</sup> / <sub>16</sub>
2	1.84	4 <sup>1</sup> / <sub>4</sub>	2 <sup>3</sup> / <sub>4</sub>	4 <sup>1</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>2</sub>
2 x 2 x 1 1/2	1.07	3 <sup>5</sup> / <sub>8</sub>	2 <sup>3</sup> / <sub>8</sub>	3 <sup>7</sup> / <sub>32</sub>	7 <sup>1</sup> / <sub>32</sub>
3	3.49	6 <sup>7</sup> / <sub>16</sub>	4 <sup>1</sup> / <sub>32</sub>	6 <sup>1</sup> / <sub>32</sub>	3 <sup>4</sup> / <sub>4</sub>
3 x 3 x 2	2.78	4 <sup>7</sup> / <sub>8</sub>	3 <sup>5</sup> / <sub>16</sub>	4 <sup>5</sup> / <sub>32</sub>	3 <sup>3</sup> / <sub>32</sub>



836  
DWV Double Long Turn T-Y  
C x C x C x C – Cast


NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES			
		C	D	J	K
1 1/2	1.25	3 <sup>5</sup> / <sub>16</sub>	2 <sup>1</sup> / <sub>8</sub>	3 <sup>5</sup> / <sub>32</sub>	7 <sup>1</sup> / <sub>32</sub>
2	0.87	3 <sup>5</sup> / <sub>16</sub>	2 <sup>1</sup> / <sub>8</sub>	3 <sup>5</sup> / <sub>32</sub>	7 <sup>1</sup> / <sub>16</sub>
2 x 2 x 1 1/2 x 1 1/2	1.96	3 <sup>5</sup> / <sub>8</sub>	2 <sup>3</sup> / <sub>8</sub>	3 <sup>7</sup> / <sub>32</sub>	7 <sup>1</sup> / <sub>32</sub>
2 x 2 x 1 1/4 x 1 1/4	2.67	3 <sup>11</sup> / <sub>16</sub>	2 <sup>3</sup> / <sub>8</sub>	3 <sup>7</sup> / <sub>32</sub>	7 <sup>1</sup> / <sub>32</sub>

## Y's continued



810  
DWV 45° Y  
C x C x C – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES			
		C	D	K	L
1 1/4	0.60	2	2	3 <sup>3</sup> / <sub>8</sub>	–
1 1/2	0.94	2 <sup>5</sup> / <sub>16</sub>	2 <sup>5</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>2</sub>	–
2	1.26	2 <sup>7</sup> / <sub>8</sub>	2 <sup>7</sup> / <sub>8</sub>	1 <sup>7</sup> / <sub>32</sub>	–
2 x 2 x 1 1/2	1.15	2 <sup>11</sup> / <sub>16</sub>	2 <sup>9</sup> / <sub>16</sub>	3 <sup>1</sup> / <sub>16</sub>	–
2 x 2 x 1 1/4	1.01	2 <sup>9</sup> / <sub>16</sub>	2 <sup>11</sup> / <sub>32</sub>	1 <sup>1</sup> / <sub>16</sub>	–
2 x 1 1/2 x 2	1.16	2 <sup>17</sup> / <sub>32</sub>	2 <sup>5</sup> / <sub>8</sub>	1 <sup>7</sup> / <sub>32</sub>	–
2 x 1 1/2 x 1 1/2	0.84	2 <sup>5</sup> / <sub>32</sub>	2 <sup>5</sup> / <sub>32</sub>	5 <sup>1</sup> / <sub>16</sub>	–
3	3.19	4 <sup>1</sup> / <sub>64</sub>	4 <sup>1</sup> / <sub>64</sub>	4 <sup>5</sup> / <sub>64</sub>	–
3 x 3 x 2	2.02	3 <sup>17</sup> / <sub>32</sub>	3 <sup>5</sup> / <sub>16</sub>	1 <sup>1</sup> / <sub>8</sub>	–
3 x 3 x 1 1/2	1.69	3 <sup>1</sup> / <sub>4</sub>	2 <sup>15</sup> / <sub>16</sub>	–	3 <sup>1</sup> / <sub>16</sub>
4	5.55	5 <sup>15</sup> / <sub>32</sub>	5 <sup>15</sup> / <sub>32</sub>	1 <sup>1</sup> / <sub>16</sub>	–
4 x 4 x 3	3.96	4 <sup>11</sup> / <sub>16</sub>	4 <sup>1</sup> / <sub>2</sub>	5 <sup>1</sup> / <sub>16</sub>	–
4 x 4 x 2	2.90	4 <sup>7</sup> / <sub>32</sub>	3 <sup>13</sup> / <sub>16</sub>	–	3 <sup>3</sup> / <sub>8</sub>




834  
DWV 45° Double Y  
C x C x C x C – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES			
		C	D	K	L
2	1.90	2 <sup>7</sup> / <sub>8</sub>	2 <sup>7</sup> / <sub>8</sub>	1 <sup>7</sup> / <sub>32</sub>	–
2 x 2 x 1 1/2 x 1 1/2	1.26	2 <sup>11</sup> / <sub>16</sub>	2 <sup>9</sup> / <sub>16</sub>	3 <sup>1</sup> / <sub>16</sub>	–
3	4.20	4 <sup>13</sup> / <sub>32</sub>	4 <sup>13</sup> / <sub>32</sub>	2 <sup>5</sup> / <sub>32</sub>	–
3 x 3 x 1 1/2 x 1 1/2	2.09	3 <sup>1</sup> / <sub>4</sub>	2 <sup>15</sup> / <sub>16</sub>	–	5 <sup>1</sup> / <sub>16</sub>

Consult price sheet for Made to Order items and for minimum order quantities.




**TRAPS**




890  
3 x 5 DWV Drum Trap  
w/Bottom Inlet  
C x F x Cleanout w/Plug – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		B	C	E
1 1/2	1.97	3 <sup>9</sup> / <sub>32</sub>	1 1/2	2 <sup>3</sup> / <sub>8</sub>




891  
3 x 6 DWV Swivel Drum Trap  
C x C x Cleanout w/Plug – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES			
		B	C	F	J
1 1/2	2.90	6 <sup>21</sup> / <sub>32</sub>	1 1/2	1	3 <sup>7</sup> / <sub>8</sub>




880  
DWV P-Trap w/Cleanout  
C x SJ x Cleanout w/Plug – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES			
		A	E	J	K
1 1/2	1.80	1 <sup>13</sup> / <sub>32</sub>	2 <sup>7</sup> / <sub>32</sub>	2 1/2	3 <sup>17</sup> / <sub>32</sub>
2	2.66	1 <sup>7</sup> / <sub>8</sub>	2 <sup>7</sup> / <sub>16</sub>	3	4 <sup>3</sup> / <sub>16</sub>




881  
DWV P-Trap  
C x SJ – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES			
		A	E	J	K
1 1/2	1.50	1 <sup>13</sup> / <sub>32</sub>	2 <sup>7</sup> / <sub>32</sub>	2 1/2	3 <sup>17</sup> / <sub>32</sub>




884  
DWV P-Trap w/Cleanout  
C x C x Cleanout w/Plug – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES			
		A	C	J	K
1 1/4	1.21	1 <sup>5</sup> / <sub>32</sub>	1 <sup>17</sup> / <sub>32</sub>	2 1/4	3 <sup>9</sup> / <sub>32</sub>
1 1/2	1.53	1 <sup>13</sup> / <sub>32</sub>	1 <sup>15</sup> / <sub>32</sub>	2 1/2	3 <sup>17</sup> / <sub>32</sub>
2	2.26	1 <sup>7</sup> / <sub>8</sub>	1 <sup>13</sup> / <sub>32</sub>	3	4 <sup>3</sup> / <sub>32</sub>
3	5.74	2 <sup>7</sup> / <sub>8</sub>	1 <sup>15</sup> / <sub>16</sub>	4	5 <sup>21</sup> / <sub>32</sub>




885  
DWV P-Trap  
C x C – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES			
		A	C	J	K
1 1/4	1.09	1 <sup>5</sup> / <sub>32</sub>	1 <sup>17</sup> / <sub>32</sub>	2 1/4	3 <sup>9</sup> / <sub>32</sub>
1 1/2	1.45	1 <sup>13</sup> / <sub>32</sub>	1 <sup>15</sup> / <sub>32</sub>	2 1/2	3 <sup>17</sup> / <sub>32</sub>
2	2.11	1 <sup>7</sup> / <sub>8</sub>	1 <sup>13</sup> / <sub>32</sub>	3	4 <sup>3</sup> / <sub>32</sub>
3	5.17	2 <sup>7</sup> / <sub>8</sub>	1 <sup>15</sup> / <sub>16</sub>	4	5 <sup>21</sup> / <sub>32</sub>




892  
DWV P-Trap w/Union Joint  
C x SJ – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES			
		A	E	J	K
1 1/2	1.86	1 <sup>1</sup> / <sub>8</sub>	3 <sup>5</sup> / <sub>32</sub>	2 <sup>5</sup> / <sub>8</sub>	3 <sup>7</sup> / <sub>16</sub>
2	2.64	1 <sup>15</sup> / <sub>32</sub>	3 <sup>13</sup> / <sub>32</sub>	3 <sup>1</sup> / <sub>8</sub>	3 <sup>29</sup> / <sub>32</sub>



892-3  
DWV P-Trap w/Union Joint  
F x SJ – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES			
		A	E	J	K
2	2.89	1 <sup>13</sup> / <sub>32</sub>	3 <sup>13</sup> / <sub>32</sub>	3 <sup>1</sup> / <sub>8</sub>	3 <sup>29</sup> / <sub>32</sub>




892-A  
DWV P-Trap w/Union Joint  
F x SJ x Cleanout w/Plug – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES			
		A	E	J	K
1 1/2	1.88	1 <sup>15</sup> / <sub>16</sub>	2 <sup>7</sup> / <sub>32</sub>	2 1/2	3 <sup>17</sup> / <sub>32</sub>

Consult price sheet for Made to Order items and for minimum order quantities.




**TRAPS** *cont.*



875-S  
DWV Trap Upturn  
M x S – Cast


NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		B	E	J
1 1/2	1.20	1 <sup>41</sup> / <sub>64</sub>	1 <sup>9</sup> / <sub>64</sub>	4

**RETURN BENDS**



878  
DWV Return Bend w/Cleanout  
C x C x Cleanout w/Plug – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		C	J	
1 1/4	0.81	1 <sup>17</sup> / <sub>32</sub>	2 <sup>1</sup> / <sub>4</sub>	–
1 1/2	0.98	1 <sup>15</sup> / <sub>32</sub>	2 <sup>1</sup> / <sub>2</sub>	–
2	1.40	1 <sup>13</sup> / <sub>32</sub>	3	–
3	3.34	1 <sup>15</sup> / <sub>16</sub>	4	–



879  
DWV Return Bend  
C x C – Cast

NOM. SIZE	APPROX. NET WT. LBS.	DIMENSIONS INCHES		
		C	J	L
1 1/4	0.76	1 <sup>17</sup> / <sub>32</sub>	2 <sup>1</sup> / <sub>4</sub>	–
1 1/2	0.90	1 <sup>15</sup> / <sub>32</sub>	2 <sup>1</sup> / <sub>2</sub>	–
1 1/2 x 1 1/2 o.d.	1.00	1 <sup>15</sup> / <sub>32</sub>	2 <sup>1</sup> / <sub>2</sub>	–
2	1.25	1 <sup>13</sup> / <sub>32</sub>	3	–
2 x 1 1/2 o.d.	1.23	1 <sup>17</sup> / <sub>32</sub>	3	1 <sup>19</sup> / <sub>32</sub>
2 x 1 1/2	1.37	1 <sup>17</sup> / <sub>32</sub>	3	1 <sup>19</sup> / <sub>32</sub>
3	2.77	1 <sup>15</sup> / <sub>16</sub>	4	–

Consult price sheet for Made to Order items and for minimum order quantities.

## Engineering Data

### Brazing Alloy

Consumption .....	42
-------------------	----

### Brazing Fittings

Dimensions .....	46
Installation Techniques .....	49-50

### Copper Fittings Dimensional Data

Solder Joing Fitting Ends .....	45
Brazing Fitting Ends.....	46
Expansion and Contraction .....	47

### Copper Tube Fittings

Brazing Information.....	42
Fitting Terms and Abbreviations.....	39
Plumbing System Failures.....	40
Rated Internal Working Pressures .....	43-44
Solder and Flux Requirements .....	42
Solder Joint Specification.....	41
Types of Joints .....	39

### Frequently Asked Questions..... 52

### Joints

Abbreviations .....	39
Brazing.....	46-47
Soldering .....	45
Types .....	39
Rated Internal Working Pressures .....	43-44

### Solder and Flux

Ratings.....	43
Requirements .....	42

### Solder Joint Fittings

Dimensions .....	45
Installation Techniques .....	48

## Installation Instructions

The Fine Art of Soldering.....	48
--------------------------------	----

The Fine Art of Brazing.....	49-50
------------------------------	-------

Polybutylene Installation.....	51
--------------------------------	----

## Numerical Index

Numerical Index .....	55
-----------------------	----



The manufacturing plants at Stuarts Draft, VA, Nacogdoches, TX and Reynosa, Mexico manufacture products under a Quality Management System conforming to the current revision of ISO-9001 International Standards

# Copper Tube Fittings

## TYPES OF JOINTS

**Flared Joint** — The principle of the flared joint was first developed for copper tube plumbing in 1928 by NIBCO. The flared type joint is wholly a mechanical means of joining copper tubes. The tube nut is placed over the end of the copper tube to be joined; the tube end then is flared out at an approximate 45 degree angle by a flaring tool. The flared end is then drawn up by the tube nut so the inside surface is tightly secured against the ball seat of the fitting. This joint can be readily dismantled at any time and is, in effect, a type of union connection. Its use is generally restricted to soft (annealed) copper tubes since hard drawn tubes would be subject to splitting when flared (if the ends were not previously annealed). The flared ends of NIBCO Flared Fittings are produced to the requirements of ASME B16.26, "Cast Copper Alloy Fittings for Flared Copper Tube."

**Solder Joint** — NIBCO pioneered the development of the solder joint and its application to the field of copper tube piping. Today the solder joint is widely adopted, as evidenced by the majority of cities and states that have written codes to include copper tube and solder joints as desirable for general plumbing, water lines, vent, stack, waste and drain lines, as well as other uses in industry. Testing has shown that often the solder joint has greater strength than the tubes being joined, depending upon the soldering alloy selected. While the method of preparing a solder joint is an exacting art to insure a full strength joint, it can be readily mastered by skilled tradesmen. It is for this reason — to insure the public of the protection afforded by properly prepared joints — that NIBCO products are marketed through the reputable sources of supply to the piping trades. Important procedures for preparing a solder joint are graphically illustrated in this catalog on page 48.

**Brazed Joint** — This type of joint has long been used wherever and whenever critical situations have been encountered in copper piping. The joint itself is completed much in the same manner as the solder joint; however, considerably more heat and several refinements of technique require separate procedures that are described further in this catalog on pages 49-50.

**Threaded Ends** — To adapt copper tube to equipment having National Standard Pipe Taper (NPT) threads or to add copper tube to existing iron pipe installations or other threaded connections, NIBCO provides fittings having both external and internal NPT threads. These threaded ends are produced to the requirements of ASME B1.20.1, "Pipe Threads, General Purpose (Inch)."

**Flanges** — To adapt copper tube to equipment having flanged connections, or to add copper tube to flanged pipe installations or other purposes, NIBCO provides flanges. The flanges are produced in two standard types widely used in this field where copper tube can serve — Class 150, comply with ASME B16.24, "Cast Copper Alloy Pipe Flanges and Flanged Fittings Class 150, 300, 400, 600, 900, 1500 and 2500"; and Class 125, which conform to MSS SP 106, "Cast Copper Alloy Flanges and Flanged Fittings Class 125, 150 and 300."

**Barbed Insert Fittings for Polybutylene (PB)** — NIBCO offers a complete line of copper barbed insert fittings for joining PB tube. The insert fittings are produced to the requirements of ASTM F 1380. Along with the insert fittings are copper crimp rings, which, when properly installed, provide a leak-tight mechanical joint. Transition fittings are available for adapting to new or existing threaded or solder joint ends.

## Fitting Terms and Abbreviations

C	Female solder cup
Ftg	Male solder end
F	Female NPT thread
M	Male NPT thread
Hose	Standard hose thread
Hub	Female end for soil pipe
Spigot	Male end for soil pipe
No Hub	Used with mechanical coupling
O.D. Tube	Actual tube outside diameter
S	Straight thread
SJ	Slip joint
FL	Flared

## WHAT MAKES A PLUMBING SYSTEM FAIL?

Failure in a copper plumbing system is rare, but may occur due to a variety of reasons. The most common causes of failure are:

1. Excessive fluid velocity causes erosion-corrosion or impingement (to strike or hit against) attack in the tube and/or fitting. For this reason, the copper plumbing industry has establish design velocity limits for copper plumbing systems to the following:

Hot Water > 140°F (60°C)	2 to 3 feet per second (0.6 to 0.9 meters per second)
Hot Water 140°F (60°C)	4 to 5 feet per second (1.2 to 1.5 meters per second)
Cold Water	5 to 8 feet per second (1.5 to 2.4 meters per second)

2. Localized high velocities and/or turbulence. The presence of a dent, tube ends which are not reamed or deburred before soldering, and sudden changes in direction can all cause localized high velocity conditions.
3. Flux Corrosion is typified by pin hole leaks, generally in the bottom of a horizontal line. Fluxes are mildly corrosive liquid or petroleum-based pastes containing chlorides of zinc and ammonia. Unless the flux is flushed from the system, it will lay in the bottom of the tube and remain active. ASTM B 813, "Liquid and Paste Fluxes for Soldering Applications of Copper and Copper-Alloy Tube," limits the corrosivity of soldering fluxes and ensures that these fluxes are flushable in cold water, which facilitates easy removal of flux residue following installation.
4. Galvanic Corrosion may be defined as the destruction of a material by electrochemical interaction between the environment and the material. Generally, it is slow but persistent in character and requires the presence of dissimilar metals. Galvanic corrosion requires the flow of an electric current between certain areas of dissimilar metal surfaces. To complete the electric circuit, there must be two electrodes, an anode and a cathode, and they must be connected by an electrolyte media (water) through which the current can pass. The amount of metal which dissolves at the anode is proportional to the number of electrons flowing, which in turn is dependent upon the potential and resistance of the two metals. The use of dissimilar metals in a plumbing system may or may not create a problem. For instance, copper and steel are perhaps the most common dissimilar metals found together in a plumbing system. In closed systems, such as a chilled or heating water piping, the use of dissimilar metals may not create a serious problem; this is because there is virtually no oxygen in the water and corrosion relations tend to be stifled. Where dissimilar metals must be used, some codes require that they should be separated by dielectric union or a similar type of fitting. The effectiveness depends upon; distance between the metals on the electromotive-force series (EMF) chart, ratio of cathode to anode area, degree of aeration, amount of agitation, temperature, presence of dissolved salts, and other factors.

### ABBREVIATED EMF SERIES

(Electromotive-Force Series; Common Piping Materials in Sea Water)

#### CATHODE (+) Passive

GOLD – Fixtures, Faucets, Plating  
 PLATINUM  
 SILVER – Brazing alloys, Silver-bearing solders  
 TITANIUM – Condenser tubes  
 MONEL (67% Ni - 33% Cu) – Specialty piping & equipment  
 CUPRO-NICKEL – Condensers, Marine, Nuclear  
 COPPER – Pressure, DWV, Gases, Air, Refrigeration, etc.  
 BRASS (85/15 - Red) – Cast fittings, Valves  
 BRASS (70/30 - Yellow) – Gas-cocks, Fittings, Connectors  
 LEAD – Solder, Pipe, Sheet, Coating, Lining  
 TIN – Solders, Coating, Lining  
 CAST IRON – Pressure, DWV  
 WROUGHT IRON – Pressure  
 MILD STEEL – Fire Protection  
 ALUMINUM – Refrigeration, Irrigation, some Solar  
 GALVANIZED STEEL – Pressure, DWV  
 ZINC – Coatings, Linings, some Fittings  
 MAGNESIUM – Water Heater Anodes, Cathodic protection for pipelines

#### ANODE (-) Active; Sacrificial Material

5. Dezincification is a type of corrosion in which brass dissolves as an alloy and the copper constituent redeposits from solution onto the surface of the brass as a metal, but in the porous form. The zinc constituent may be carried away from the brass as a soluble salt, or may be deposited in place as an insoluble compound. Dezincification is normally associated with brass valves where the zinc content exceeds 15%. Generally, areas of high stress, such as valve stems and gate valve bodies, are primary targets of attack.
6. On rare occasion problems of corrosion by aggressive water, possibly aggravated by poor design or workmanship, do exist. Aggressive, hard well waters that cause pitting can be identified by chemical analysis and treated to bring their composition within acceptable limits. Typically these hard waters are found to have high total dissolved solids (t.d.s.) including sulfates and chlorides, a pH in the range of 7.2 to 7.8, a high content of carbon dioxide (CO<sub>2</sub>) gas (over 10 parts per million, ppm), and the presence of dissolved oxygen (D.O.) gas. Soft acidic waters can cause the annoying problem of green staining of fixtures or "green water". Raising the pH of such waters to a value of about 7.2 or more usually solves the problem, but a qualified water treatment specialist should be consulted.
7. Aggressive soil conditions can be a cause for external corrosion of copper piping systems. Non-uniform soil characteristics, such as different soil aeration, resistivity, or moisture properties, between adjacent sections of tube can create galvanic corrosion cells. Soils contaminated with high concentrations of road salts or fertilizers containing ammonia, chlorides, and nitrogen are known to combine with water to form acids. Any metal pipe laid in ash or cinders is subject to attack by the acid generated when sulfur compounds combine with water to form sulfuric acid.

U.S. customary units in this document are the standard; the metric units are provided for reference only. The values stated in each system are not exact equivalents.

# Copper Tube Fittings continued

## SOLDER JOINT SPECIFICATION

- Soldering Clearance** (between the outside of the tube and the inside diameter of the solder cup) **and the Depth of the Solder Cup** (into which the tube is inserted).

**Chart 1 – Soldering Clearance and Solder Cup Depth**

Nominal Size of Fitting (Inches)	Maximum I.D. of Fitting		Minimum O.D. of Tube		Maximum Clearance for Soldering		Depth of Solder Cup	
	Inch	(mm)	Inch	(mm)	Inch	(mm)	Inch	(mm)
1/4	0.381	(9.66)	0.374	(9.50)	0.007	(0.18)	0.31	(7.9)
3/8	0.506	(12.85)	0.499	(12.67)	0.007	(0.18)	0.38	(9.7)
1/2	0.631	(16.03)	0.622	(15.80)	0.009	(0.23)	0.50	(12.7)
5/8	0.756	(19.20)	0.749	(19.02)	0.007	(0.18)	0.62	(15.7)
3/4	0.881	(22.38)	0.872	(22.20)	0.009	(0.23)	0.75	(19.1)
1	1.132	(28.75)	1.123	(28.54)	0.009	(0.23)	0.91	(23.1)
1 1/4	1.382	(35.10)	1.373	(34.88)	0.009	(0.23)	0.97	(24.6)
1 1/2	1.633	(41.48)	1.623	(41.22)	0.010	(0.25)	1.09	(27.7)
2	2.133	(54.18)	2.123	(53.92)	0.010	(0.25)	1.34	(34.0)
2 1/2	2.633	(66.88)	2.623	(66.62)	0.010	(0.25)	1.47	(37.3)
3	3.133	(79.58)	3.123	(79.32)	0.010	(0.25)	1.66	(42.2)
3 1/2	3.633	(92.28)	3.623	(92.02)	0.010	(0.25)	1.91	(48.5)
4	4.133	(104.98)	4.123	(104.72)	0.010	(0.25)	2.16	(54.9)
5	5.133	(130.38)	5.123	(130.12)	0.010	(0.25)	2.66	(67.6)
6	6.133	(155.78)	6.123	(155.52)	0.010	(0.25)	3.09	(78.5)

The National Bureau of Standards Report BMS58, "Strength of Soft-Soldered Joints in Copper Tubing," reporting on tests conducted with 3/4-inch tubing and fitting, says "When the clearance is greater than 0.010 inch (0.25 mm), there is difficulty in filling the joint properly."

- Depth of Solder Penetration** drastically affects the breaking load of the joint. When there is too great a soldering clearance, there is no capillary flow to assure complete solder penetration. As shown in the chart below, the holding power of the 3/4-inch joint is directly proportional to the depth of solder penetration.

For example: If you get only one-third penetration, you get approximately one-third the strength needed to assure complete satisfaction.


**Chart 2 – Type K 3/4" Tubing**



Solder penetration of one-third the cup depth — breaking load, approximately 2,100 lb. (955 kg)



Solder penetration of the entire cup depth — breaking load, approximately 7,000 lb. (3175 kg)



## HOW TO BE SURE OF PROPER TOLERANCES

It is apparent that all of the scientific apparatus used to test tube and fittings, according to the dimensions indicated in Chart 1, would be impractical to use on the job. It is therefore essential that you install tube and fittings manufactured by companies known to be dedicated to the highest quality control standards. Should you encounter a condition where there is difficulty in filling the joint properly, NIBCO will analyze the trouble without charge. Just send six inches of the tube, along with the fitting and our technicians will provide you with an authoritative report.

U.S. customary units in this document are the standard; the metric units are provided for reference only. The values stated in each system are not exact equivalents.

**BRAZING INFORMATION**

Copper Water Tube Size (In Inches)	Brazing <sup>A</sup> Filler Required Inches (mm)		Torch Tip Drill Size No.	For Estimating Purposes					
				Acetylene Consumption C.F.H. (C.M.H.)		Oxygen Pressure (Approx.) PSI (kPa)		Acetylene Pressure (Approx.) PSI (kPa)	
1/4	0.25 <sup>B</sup>	(6.4)	54	15.9	(0.5)	4	(27)	4	(27)
3/8	0.38 <sup>B</sup>	(9.7)	54	15.9	(0.5)	4	(27)	4	(27)
1/2	0.50	(12.7)	51	24.8	(0.7)	5	(34)	5	(34)
5/8	0.62	(15.7)	51	24.8	(0.7)	5	(34)	5	(34)
3/4	1.00	(25.0)	51	24.8	(0.7)	5	(34)	5	(34)
1	1.60	(41.0)	48	31.6	(0.9)	6	(41)	6	(41)
1 1/4	2.00	(51.0)	48	31.6	(0.9)	6	(41)	6	(41)
1 1/2	2.60	(66.0)	44	38.7	(1.1)	7	(48)	7	(48)
2	4.40	(112.0)	40	60.0	(1.7)	7	(48)	7	(48)
2 1/2	5.90	(150.0)	40	60.0	(1.7)	7	(48)	7	(48)
3	7.90	(200.0)	35	70.0	(2.0)	7 1/2	(52)	7 1/2	(52)
3 1/2	10.50	(207.0)	35	70.0	(2.0)	7 1/2	(52)	7 1/2	(52)
4	13.50	(343.0)	30	88.5	(2.5)	9	(62)	9	(62)
5	20.50	(521.0)	30	88.5	(2.5)	9	(62)	9	(62)
6	28.50	(724.0)	30	88.5	(2.5)	9	(62)	9	(62)

<sup>A</sup> Approximate consumption when brazing one cup of the fitting. Actual consumption depends on workmanship.  
 For filler sizes shown, one pound of filler alloy provides 1,068 inches (27.13 mm) of 1/16-inch wire or 475 inches (12,065 mm) of 3/32-inch wire.  
<sup>B</sup> 1/16-inch (1.59 mm) diameter wire; all other is 3/32-inch (2.38 mm) diameter.

**SOLDER AND FLUX REQUIREMENTS**

Nom. Size Joint (In Inches)	Solder Required, LB (kg)	
	General Use	Drainage Use
1/4	0.097	—
3/8	0.159	—
1/2	0.261	—
5/8	0.389	—
3/4	0.548	—
1	0.856	—
1 1/4	1.115	1.2 (0.5)
1 1/2	1.480	1.4 (0.6)
2	2.380	1.5 (0.7)
2 1/2	3.225	—
3	4.335	2.8 (1.3)
3 1/2	5.786	—
4	7.446	4.2 (1.9)
5	11.392	—
6	15.815	—
8	26.955	—

Solder requirements in this table are based on estimate of weight of solder used to prepare 100 solder joints of sizes shown.

Two (2) ounces (0.06 kg) of solder flux will be required for each pound (0.45 kg) of solder.

U.S. customary units in this document are the standard; the metric units are provided for reference only. The values stated in each system are not exact equivalents.

# Copper Tube Fittings continued

## RATED INTERNAL WORKING PRESSURES OF JOINTS MADE WITH COPPER WATER TUBE AND SOLDER TYPE FITTINGS, PSI (BAR)

Joining Material	Working Temperature °F °C		Maximum Gauge Working Pressure for Standard Water Tube Sizes [Note (1)]								Saturated Steam LB (kg) All Sizes
			1/8" through 1" PSI BAR		1 1/4" through 2" PSI BAR		2 1/2" through 4" PSI BAR		5" through 8" PSI BAR		
Alloy Sn50 50-50 Tin-Lead solder [Notes (2), (3)]	100	38	200 (14)	175 (12)	150 (10)	135 (9)	100 (6)			15	
	150	66	150 (10)	125 (9)	100 (7)	90 (6)	70 (5)				
	200	93	100 (7)	90 (6)	75 (5)	70 (5)	50 (3)				
	250	121	85 (6)	75 (5)	50 (3)	45 (3)	40 (3)				
Alloy Sb5 95-5 Tin-Antimony solder [Note (4)]	100	38	1090 <sup>(9)</sup> (75)	850 <sup>(8)</sup> (59)	705 <sup>(9)</sup> (49)	660 <sup>(8)</sup> (46)	340 (23)			15	
	150	66	625 <sup>(10)</sup> (43)	485 <sup>(10)</sup> (34)	405 <sup>(10)</sup> (28)	375 <sup>(10)</sup> (26)	280 (19)				
	200	93	505 <sup>(11)</sup> (35)	395 <sup>(10)</sup> (27)	325 <sup>(10)</sup> (32)	305 <sup>(10)</sup> (21)	230 (16)				
	250	121	270 (19)	210 (15)	175 (12)	165 (11)	120 (8)				
Alloy E	100	38	710 <sup>(10)</sup> (49)	555 <sup>(10)</sup> (38)	460 <sup>(10)</sup> (32)	430 <sup>(10)</sup> (30)	320 (22)			15	
	150	66	475 <sup>(11)</sup> (33)	370 <sup>(10)</sup> (26)	305 <sup>(10)</sup> (21)	285 <sup>(11)</sup> (20)	215 (15)				
	200	93	375 (26)	290 (20)	240 <sup>(11)</sup> (17)	225 <sup>(11)</sup> (16)	170 (12)				
	250	121	320 (22)	250 (17)	205 (14)	195 (13)	145 (9)				
Alloy HB [Note (6)]	100	38	1035 <sup>(9)</sup> (71)	805 <sup>(8)</sup> (56)	670 <sup>(8)</sup> (46)	625 <sup>(9)</sup> (43)	340 (23)			15	
	150	66	710 <sup>(10)</sup> (49)	555 <sup>(10)</sup> (38)	460 <sup>(10)</sup> (32)	430 <sup>(10)</sup> (30)	320 (22)				
	200	93	440 <sup>(11)</sup> (30)	345 <sup>(11)</sup> (24)	285 <sup>(11)</sup> (20)	265 <sup>(11)</sup> (18)	200 (14)				
	250	121	430 <sup>(11)</sup> (30)	335 <sup>(11)</sup> (23)	275 <sup>(11)</sup> (19)	260 <sup>(11)</sup> (18)	195 (13)				
Joining materials at or above 593°C [Note (7)]	Pressure-temperature ratings consistent with the materials and procedures employed.										

**GENERAL NOTE:**

For extremely low working temperatures in the 0°F to 200°F range, it is recommended that a joint material melting at or above 1000°F be employed [see Note (5)].

**NOTES:**

- (1) Standard water tube sizes per ASTM B 88
- (2) ASTM B 32 Alloy Grade Sn50
- (3) The Safe Drinking Water Act Amendment of 1986 prohibits the use of any solder having a lead content in excess of 0.2% in potable water systems.
- (4) ASTM B 32 Alloy Grade Sb5
- (5) ASTM B 32 Alloy Grade E
- (6) ASTM B 32 Alloy Grade HB
- (7) These joining materials are defined as *brazing alloys* by the American Welding Society.
- (8) The solder joint exceeds the strength of Types K, L & M tube in drawn and annealed tempers.
- (9) The solder joint exceeds the strength of Types L & M tube in drawn temper and Type K tube in annealed temper.
- (10) The solder joint exceeds the strength of Type M tube in drawn temper and Types L & K in annealed temper.
- (11) The solder joint exceeds the strength of Type L tube in annealed temper.

## RATED INTERNAL WORKING PRESSURES OF JOINTS MADE WITH FLARED FITTINGS AND COPPER WATER TUBE

Nominal Size Joint (In Inches)	Temperature, °F (°C) <sup>A</sup>	Pressure, PSI (BAR) <sup>A</sup>
3/8, 1/2, 3/4, 1, 1 1/4, 1 1/2, 2	100 (38)	175 (12)

<sup>A</sup>ASME B16.26

## RATED INTERNAL WORKING PRESSURES OF POLYBUTYLENE TUBE AND COPPER BARBED INSERT FITTINGS

Nominal Size Joint (In Inches)	Temperature, °F (°C)		Pressure, PSI (BAR)
	73 (23)	140 (60)	
3/8, 1/2, 3/4, 1	73 (23)	140 (60)	200 (14)
	140 (60)	180 (82)	160 (11)
	180 (82)	200 (93)	100 (7)
	200 (93)		80 (5)

U.S. customary units in this document are the standard; the metric units are provided for reference only. The values stated in each system are not exact equivalents.

**RATED INTERNAL WORKING PRESSURE<sup>1</sup> FOR COPPER FITTINGS, PSI (BAR)**

Nominal Water Tube Size (In Inches)	Water Temperature Range						
	-20° to 100°F (-29° to 38°C)	150°F (66°C)	200°F (95°C)	250°F (120°C)	300°F (149°C)	350°F (177°C)	400°F (204°C)
1/4	912 (62)	775 (53)	729 (50)	729 (50)	714 (49)	608 (42)	456 (31)
3/8	779 (54)	662 (46)	623 (43)	623 (43)	610 (42)	519 (36)	389 (27)
1/2	722 (50)	613 (42)	577 (40)	577 (40)	565 (39)	481 (33)	361 (25)
5/8	631 (43)	537 (37)	505 (35)	505 (35)	495 (34)	421 (29)	316 (21)
3/4	582 (40)	495 (34)	466 (32)	466 (32)	456 (31)	388 (27)	291 (20)
1	494 (34)	420 (29)	395 (27)	395 (27)	387 (26)	330 (23)	247 (17)
1 1/4	439 (30)	373 (26)	351 (24)	351 (24)	344 (23)	293 (20)	219 (15)
1 1/2	408 (28)	347 (24)	327 (23)	327 (23)	320 (22)	272 (19)	204 (14)
2	364 (25)	309 (21)	291 (20)	291 (20)	285 (20)	242 (17)	182 (13)
2 1/2	336 (23)	285 (20)	269 (19)	269 (19)	263 (18)	224 (15)	168 (12)
3	317 (22)	270 (19)	254 (17)	254 (17)	248 (17)	211 (15)	159 (11)
3 1/2	304 (21)	258 (18)	243 (17)	243 (17)	238 (16)	202 (14)	152 (10)
4	293 (20)	249 (17)	235 (16)	235 (16)	230 (16)	196 (13)	147 (10)
5	269 (19)	229 (16)	215 (15)	215 (15)	211 (15)	179 (12)	135 (9)
6	251 (17)	213 (15)	201 (14)	201 (14)	196 (14)	167 (12)	125 (8)
8	270 (19)	230 (16)	216 (15)	216 (15)	212 (15)	180 (12)	135 (9)

<sup>1</sup> The fitting pressure rating applies to the largest opening of the fitting.

**RATED INTERNAL WORKING PRESSURES OF CAST COPPER ALLOY FLANGES AND FLANGED FITTINGS**

Nominal Size Joint (In Inches)	Temperature °F (°C) <sup>A</sup>	Pressure (PSI)		
		Class 125 <sup>A,B</sup>	Class 150 <sup>B</sup>	Class 150 <sup>A,C</sup>
1/2, 3/4, 1, 1 1/4, 1 1/2, 2, 2 1/2, 3, 4, 5, 6, 8 (also 10" for Class 125)	0 – 150 (0 – 66)	105 (7)	210 (14)	225 (15)
	175 (79)	100 (7)	205 (14)	220 (15)
	200 (93)	95 (7)	195 (13)	210 (15)
	225 (107)	90 (6)	190 (13)	205 (14)
	250 (121)	90 (6)	180 (12)	195 (13)
	275 (135)	85 (6)	175 (12)	190 (13)
	300 (149)	85 (6)	170 (12)	180 (12)
	350 (177)	75 (5)	150 (10)	165 (11)
	406 (208)	70 (5)	140 (9)	150 (10)

<sup>A</sup> MSS SP-106

<sup>B</sup> ASTM B584, UNS C83800 and UNS C84400

<sup>C</sup> ASTM B62, UNS C83600 and ASTM B584, UNS C83600

U.S. customary units in this document are the standard; the metric units are provided for reference only. The values stated in each system are not exact equivalents.



# Copper Fittings Dimensional Data

The mechanics of making both the solder joint and the brazing joint are comparatively similar. Complete instructions on proper techniques of both of these joining methods are outlined in this catalog on pages 48-50.

A very important consideration in Copper Piping is the selection of the proper bonding medium. As a general rule, the working temperature of the installation is a more important consideration than the working pressures. If the working temperature is not over 250°F (121°C), either 50-50%\* or 95-5% solder can be used successfully. However, if the temperature exceeds 250°F (121°C), a low temperature brazing alloy should be used, with a melting temperature somewhat in excess of 1000°F (538°C).

According to BMS report No. 58, joints made with tin or tin-alloy solders should not be subject continuously to temperatures above 250°F (121°C). A number of brazing alloys are available and a careful study should be made in every case to determine the proper alloy for the particular application.

\*The Safe Drinking Water Act Amendment of 1986 prohibits the use in potable water systems of any solder having a lead content in excess of 0.2%.

## DIMENSIONAL DATA – SOLDER JOINT FITTING ENDS

Nominal Water Tube Size (In Inches)	Solder Joint Fittings – Tolerances						Solder Joint Fittings Copper Alloy – Pressure <sup>1,2</sup>		Solder Joint Fittings Copper Alloy – Drainage <sup>3,4</sup>							
	Male End (Fitting Connector) Diameter		Female End (Solder Cup) Diameter				Fitting End Length		Solder Cup Length		Fitting End Length		Solder Cup Length			
	Min. Inch	Max. (mm)	Min. Inch	Max. (mm)	Min. Inch	Max. (mm)	Min. Inch	Max. (mm)	Min. Inch	Max. (mm)	Min. Inch	Max. (mm)	Min. Inch	Max. (mm)		
1/8	0.248	(6.30)	0.251	(6.38)	0.252	(6.40)	0.256	(6.50)	0.31	(7.9)	0.25	(6.4)	N/A	N/A	N/A	N/A
1/4	0.373	(9.47)	0.376	(9.55)	0.377	(9.58)	0.381	(9.68)	0.38	(9.7)	0.31	(7.9)	N/A	N/A	N/A	N/A
3/8	0.497	(12.62)	0.501	(12.73)	0.502	(12.75)	0.506	(12.85)	0.44	(11.2)	0.38	(9.7)	N/A	N/A	N/A	N/A
1/2	0.622	(15.80)	0.626	(15.90)	0.627	(15.93)	0.631	(16.03)	0.56	(14.2)	0.50	(12.7)	N/A	N/A	N/A	N/A
5/8	0.747	(18.97)	0.751	(19.08)	0.752	(19.10)	0.756	(19.20)	0.69	(17.5)	0.62	(15.7)	N/A	N/A	N/A	N/A
3/4	0.872	(22.15)	0.876	(22.25)	0.877	(22.28)	0.881	(22.38)	0.81	(20.6)	0.75	(19.1)	N/A	N/A	N/A	N/A
1	1.122	(28.50)	1.127	(28.63)	1.128	(28.65)	1.132	(28.75)	0.97	(24.6)	0.91	(23.1)	N/A	N/A	N/A	N/A
1 1/4	1.372	(34.85)	1.377	(34.98)	1.378	(35.00)	1.382	(35.10)	1.03	(26.2)	0.97	(24.6)	0.56	(14.2)	0.50	(12.7)
1 1/2	1.621	(41.17)	1.627	(41.33)	1.628	(41.35)	1.633	(41.48)	1.16	(29.5)	1.09	(27.7)	0.62	(15.7)	0.56	(14.2)
2	2.121	(53.87)	2.127	(54.03)	2.128	(54.05)	2.133	(54.18)	1.41	(35.8)	1.34	(34.0)	0.69	(17.5)	0.62	(15.7)
2 1/2	2.621	(66.57)	2.627	(66.73)	2.628	(66.75)	2.633	(66.88)	1.53	(38.9)	1.47	(37.3)	N/A	N/A	N/A	N/A
3	3.121	(79.27)	3.127	(79.43)	3.128	(79.45)	3.133	(79.58)	1.72	(43.7)	1.66	(42.2)	0.81	(20.6)	0.75	(19.1)
3 1/2	3.621	(91.97)	3.627	(92.13)	3.628	(92.15)	3.633	(92.28)	1.97	(50.0)	1.91	(48.5)	N/A	N/A	N/A	N/A
4	4.121	(104.67)	4.127	(104.83)	4.128	(104.85)	4.133	(104.98)	2.22	(56.4)	2.16	(54.9)	1.06	(26.9)	1.00	(25.4)
5	5.121	(130.07)	5.127	(130.23)	5.128	(130.25)	5.133	(130.38)	2.72	(69.1)	2.66	(67.6)	1.31	(33.3)	1.25	(31.8)
6	6.121	(155.47)	6.127	(155.63)	6.128	(155.65)	6.133	(155.78)	3.22	(81.8)	3.09	(78.5)	1.62	(41.1)	1.50	(38.1)
8	8.119	(206.22)	8.127	(206.43)	8.128	(206.45)	8.133	(206.58)	4.09	(103.9)	3.97	(100.8)	2.12	(53.8)	2.00	(50.8)
10	10.119	(257.02)	10.127	(257.23)	10.128	(257.25)	10.133	(257.38)	4.12	(104.6)	4.00	(101.6)	N/A	N/A	N/A	N/A
12	12.119	(307.82)	12.127	(308.03)	12.128	(308.05)	12.133	(308.18)	4.62	(117.3)	4.50	(114.3)	N/A	N/A	N/A	N/A

<sup>1</sup> As shown Standard ASME B16.18

<sup>2</sup> As shown Standard ASME B16.22

<sup>3</sup> As shown Standard ASME B16.23

<sup>4</sup> As shown Standard ASME B16.29

U.S. customary units in this document are the standard; the metric units are provided for reference only. The values stated in each system are not exact equivalents.

**DIMENSIONAL DATA – BRAZING FITTING ENDS**

Nominal Water Tube Size (In Inches)	Male End (Fitting Connector) Diameter				Female End (Brazing Cup) Diameter				Fitting End Length		Solder Cup Length	
	Min.		Max.		Min.		Max.		Min.		Min.	
	Inch	(mm)	Inch	(mm)	Inch	(mm)	Inch	(mm)	Inch	(mm)	Inch	(mm)
1/4	0.373	(9.47)	0.376	(9.55)	0.377	(9.58)	0.381	(9.68)	0.23	(5.8)	0.17	(4.3)
3/8	0.497	(12.62)	0.501	(12.73)	0.502	(12.75)	0.506	(12.85)	0.26	(6.6)	0.20	(5.1)
1/2	0.622	(15.80)	0.626	(15.90)	0.627	(15.93)	0.631	(16.03)	0.28	(7.1)	0.22	(5.6)
5/8	0.747	(18.97)	0.751	(19.08)	0.752	(19.10)	0.756	(19.20)	N/A	N/A	N/A	N/A
3/4	0.872	(22.15)	0.876	(22.25)	0.877	(22.28)	0.881	(22.38)	0.31	(7.9)	0.25	(6.4)
1	1.122	(28.50)	1.127	(28.63)	1.128	(28.65)	1.132	(28.75)	0.34	(8.6)	0.28	(7.1)
1 1/4	1.372	(34.85)	1.377	(34.98)	1.378	(35.00)	1.382	(35.10)	0.37	(9.4)	0.31	(7.9)
1 1/2	1.621	(41.17)	1.627	(41.33)	1.628	(41.35)	1.633	(41.48)	0.40	(10.2)	0.34	(8.6)
2	2.121	(53.87)	2.127	(54.03)	2.128	(54.05)	2.133	(54.18)	0.47	(11.9)	0.40	(10.2)
2 1/2	2.621	(66.57)	2.627	(66.73)	2.628	(66.75)	2.633	(66.88)	0.53	(13.5)	0.47	(11.9)
3	3.121	(79.27)	3.127	(79.43)	3.128	(79.45)	3.133	(79.58)	0.59	(15.0)	0.53	(13.5)
3 1/2	3.621	(91.97)	3.627	(92.13)	3.628	(92.15)	3.633	(92.28)	0.65	(16.5)	0.59	(15.0)
4	4.121	(104.67)	4.127	(104.83)	4.128	(104.85)	4.133	(104.98)	0.72	(18.3)	0.64	(16.3)
5	5.121	(130.07)	5.127	(130.23)	5.128	(130.25)	5.133	(130.38)	0.81	(20.6)	0.73	(18.5)
6	6.121	(155.47)	6.127	(155.63)	6.128	(155.65)	6.133	(155.78)	0.94	(23.9)	0.83	(21.1)
8	8.119	(206.22)	8.127	(206.43)	8.128	(206.45)	8.133	(206.58)	1.28	(32.5)	1.17	(29.7)
10	10.119	(257.02)	10.127	(257.23)	10.128	(257.25)	10.133	(257.38)	N/A	N/A	N/A	N/A
12	12.119	(307.82)	12.127	(308.03)	12.128	(308.05)	12.133	(308.18)	N/A	N/A	N/A	N/A


<sup>1</sup> In accordance with MS SP-73

U.S. customary units in this document are the standard; the metric units are provided for reference only. The values stated in each system are not exact equivalents.


**EXPANSION AND CONTRACTION**

In the majority of low-pressure heating systems employing copper tube and installed in small houses or private dwellings, provision for expansion and contraction is relatively simple. Mains, risers, and branches to radiators should be free or floating at one end of the line. Holes should be large enough to permit free movement of the tube, and care should be exercised so that pipe hangers and supports permit unrestricted movement and do not anchor the tube. Wrought copper tube hangers that are both practicable and neat in appearance are available.

Unusually long runs of copper tubing should be provided with an expansion bend or loop. By bending soft temper copper tube, a simple form of expansion loop can be made. With the addition of combination flared-tube to solder joint fittings, as illustrated in Figure 1, these types of loops can be used when space or other limitations exist. The correct proportions of such expansion loop to meet various conditions are shown in the accompanying table.



**FIGURE 1**



The above chart is calculated using 10ft (3.05m) of copper tubing as the reference point. You may use it as follows: 100ft (30.5m) of copper tube, with a 200°F (93.3°C) temperature change. Reference point .2256 inches for 10ft, (5.73mm for 3.05m), multiply by 10 for 100ft (30.5m), resulting in an answer of 2.256 inches (57.3mm) of expansion or contraction.

NOTE: Calculations for expansion and contraction should be based on the average coefficient of expansion of copper which is 0.0000094 per °F (0.00001692 per °C) between 77°F and 212°F (25°C and 100°C). For example, the expansion for each 10ft (3.05m) of any size of tube heated from room temperature of 70°F (21.1°C) to 170°F (76.7°C), that is, 100°F (55.6°C) rise, is:

$$\begin{matrix} \text{Rise} & & & & \text{Coefficient} \\ 100^{\circ}\text{F} & \times & 10\text{ft} & \times & 12 \text{ inches} & \times & 0.000094 & = & 0.1128 \text{ in.} \\ (55.6^{\circ}\text{C}) & & (3.05\text{m}) & & (1000\text{mm}) & & (0.00001692) & & (2.87\text{mm}) \end{matrix}$$

**RADII OF COILED EXPANSION LOOPS AND DEVELOPED LENGTHS OF EXPANSION OFFSETS**

Nominal Tube Size	Expected Expansion															
	1/2		1		1 1/2		2		2 1/2		3		3 1/2		4	
	R	L	R	L	R	L	R	L	R	L	R	L	R	L	R	L
	Inch (mm)	Inch (mm)	Inch (mm)	Inch (mm)	Inch (mm)	Inch (mm)	Inch (mm)	Inch (mm)	Inch (mm)	Inch (mm)	Inch (mm)	Inch (mm)	Inch (mm)	Inch (mm)	Inch (mm)	Inch (mm)
1/4	6 (152.4)	38 (965.2)	9 (228.6)	54 (1371.6)	11 (279.4)	66 (1676.4)	12 (304.8)	77 (1955.8)	14 (355.6)	86 (2184.4)	15 (381.0)	94 (2387.6)	16 (406.4)	102 (2590.8)	17 (431.8)	109 (2768.6)
3/8	7 (177.8)	44 (1117.6)	10 (254.0)	63 (1600.2)	12 (304.8)	77 (1955.8)	14 (355.6)	89 (2260.6)	16 (406.4)	99 (2514.6)	18 (457.2)	111 (2819.4)	19 (482.6)	122 (3098.8)	21 (533.4)	131 (3327.4)
1/2	8 (203.2)	50 (1270.0)	11 (279.4)	70 (1778.0)	14 (355.6)	89 (2260.6)	16 (406.4)	99 (2514.6)	18 (457.2)	111 (2819.4)	19 (482.6)	122 (3098.8)	21 (533.4)	131 (3327.4)	22 (558.8)	140 (3556.0)
3/4	9 (228.6)	59 (1498.6)	13 (330.2)	83 (2108.2)	16 (406.4)	101 (2565.4)	19 (482.6)	117 (2971.8)	21 (533.4)	131 (3327.4)	23 (584.2)	143 (3632.2)	25 (635.0)	155 (3937.0)	26 (660.4)	166 (4216.4)
1	11 (279.4)	67 (1701.8)	15 (381.0)	94 (2387.6)	18 (457.2)	115 (2921.0)	21 (533.4)	133 (3378.2)	24 (609.6)	149 (3794.6)	26 (660.4)	163 (4140.2)	28 (711.2)	176 (4470.4)	30 (762.0)	188 (4775.2)
1 1/2	13 (330.2)	80 (2032.0)	18 (457.2)	113 (2870.2)	22 (558.8)	138 (3505.2)	25 (635.0)	160 (4064.0)	29 (736.6)	179 (4546.6)	31 (787.4)	196 (4978.4)	34 (863.6)	212 (5394.8)	36 (914.4)	226 (5740.4)
2	15 (381.0)	91 (2311.4)	21 (533.4)	129 (3276.6)	25 (635.0)	158 (4013.2)	29 (736.6)	183 (4648.2)	33 (838.2)	205 (5207.0)	36 (914.4)	224 (5689.6)	39 (990.6)	242 (6146.8)	41 (1041.4)	259 (6578.6)
2 1/2	16 (406.4)	102 (2590.8)	23 (584.2)	144 (3657.6)	28 (711.2)	176 (4470.4)	32 (812.8)	203 (5156.2)	36 (914.4)	227 (5765.8)	40 (1016.0)	249 (6324.6)	43 (1092.2)	269 (6832.6)	46 (1168.4)	288 (7315.2)
3	18 (457.2)	111 (2819.4)	25 (635.0)	157 (3987.8)	30 (762.0)	191 (4851.4)	35 (889.0)	222 (5638.8)	40 (1016.0)	248 (6299.2)	43 (1092.2)	272 (6908.8)	47 (1193.8)	293 (7442.2)	50 (1270.0)	314 (7975.6)
3 1/2	19 (482.6)	120 (3048.0)	27 (685.8)	169 (4292.6)	33 (838.2)	206 (5232.4)	38 (965.2)	239 (6070.6)	43 (1092.2)	267 (6781.8)	47 (1193.8)	293 (7442.2)	50 (1270.0)	316 (8026.4)	54 (1371.6)	338 (8585.2)
4	20 (508.0)	128 (3251.2)	29 (736.6)	180 (4572.0)	35 (889.0)	220 (5588.0)	41 (1041.4)	255 (6477.0)	45 (1143.0)	285 (7239.0)	50 (1270.0)	312 (7924.8)	54 (1371.6)	337 (8559.8)	57 (1447.8)	361 (9169.4)
5	23 (584.2)	142 (3606.8)	32 (812.8)	201 (5105.4)	39 (990.6)	245 (6223.0)	45 (1143.0)	284 (7213.6)	51 (1295.4)	318 (8077.2)	55 (1397.0)	348 (8839.2)	60 (1524.0)	376 (9550.4)	64 (1625.6)	402(10210.8)


U.S. customary units in this document are the standard; the metric units are provided for reference only. The values stated in each system are not exact equivalents.

# The Fine Art of Soldering


When adjoining surfaces of copper and copper alloys meet under proper conditions of cleanliness and temperature, solder will make a perfect adhesion. The strength of joint is equal to or even greater than the strength of tube alone. Surface tension seals the joint. Capillary attraction draws solder into, around, and all about the joint. It's easy to learn to make a perfect solder joint when you use NIBCO Fittings.

## WITH 95-5 SOLDER AND INTERMEDIATELY CORROSIVE FLUX

1. Cut tube end square, ream, burr and size.



2. Use sand cloth or steel wire brush to clean tube and cup to a bright metal finish.



3. Apply solder flux to outside of tube and inside of cup of fitting carefully so that surfaces to be joined are completely covered. **Use flux sparingly.**



4. Apply flame to the fitting to heat tube and solder cup of fitting until solder melts when placed at joint of tube and fitting.



5. Remove flame and feed solder into the joint at one or two points until a ring of solder appears at the end of the fitting. The correct amount of solder is approximately equal to  $1\frac{1}{2}$  the diameter of the fitting...  $\frac{3}{4}$ " (20mm) solder for  $\frac{1}{2}$ " fitting, etc.



6. Remove excess solder with a small brush or wiping cloth while the solder is plastic.



# The Fine Art of Brazing

Best results will be obtained by a skilled operator employing the step-by-step brazing technique that follows:

1. The tube should be cut to desired length with a square cut, preferably in a square-end sawing vise. The cutting wheel of the type specifically designed for cutting copper tube will also do a satisfactory job. The tube should be the exact length needed, so that the tube will enter the cup of the fitting all the way to the shoulder of the cup. Remove all slivers and burrs left from cutting the tube, by reaming and filing, both inside and outside.


2. To make a proper brazing joint, the clearance between the solder cup and the tube should be approximately 0.001" to 0.010" (0.0254mm to 0.254mm). Maintaining a good fit on parts to be brazed insures:

**Ease of Application** — Excessively wide tolerances tend to break capillary force; and, as a result the alloy will either fail to flow throughout the joint or may flush out of the joint.

**Corrosion Resistance** — There is also a direct relation between the corrosion resistance of a joint and the clearance between members.

**Economy** — If brazing alloys are to be used economically, they, of necessity, must be applied in the joint proper and in minimum quantities, using merely enough alloy to fill the area between the members.


3. The surfaces to be joined must be clean and free from oil, grease and heavy oxides. The end of the tube need be cleaned only for a distance slightly more than it is to enter the cup. Special wire brushes designed to clean tube ends may be used, but they should be carefully used so that an excessive amount of metal will not be removed from the tube.



Fine sand cloth or emery cloth may also be used with the same precautions. The cleaning should not be done with steel wool, because of the likelihood of leaving small slivers of the steel or oil in the joint.

4. The cup of the fitting should be cleaned by methods similar to those used for the tube end, and care should be observed in removing residues of the cleaning medium.

Attempting to braze a contaminated or an improperly cleaned surface will result in an unsatisfactory joint. Brazing alloys will not flow over or bond to oxides; and oily or greasy surfaces tend to repel fluxes, leaving bare spots which will oxidize, resulting in voids and inclusions.




5. Flux should be applied to the tube and solder cup sparingly and in a fairly thin consistency. Avoid flux on areas not cleaned. Particularly avoid getting excess flux into the inside of the tube itself. Flux has three principal functions to perform:


A. It prevents the oxidation of the metal surfaces during the heating operation by excluding oxygen.

B. It absorbs and dissolves residual oxides that are on the surface and those oxides which may form during the heating operation.

C. It assists in the flow of the alloy by presenting a clean nascent surface for the melted alloy to flow over. In addition, it is an excellent temperature indicator, especially if an indicating flux is used.




6. Immediately after fluxing, the parts to be brazed should be assembled. If fluxed parts are allowed to stand, the water in the flux will evaporate, and dried flux is liable to flake off, exposing the metal surfaces to oxidation from the heat. Assemble the joint by inserting the tube into the cup, hard against the stop. The assembly should be firmly supported so that it will remain in alignment during the brazing operation.



7. Brazing is started by applying heat to the parts to be joined. The preferred method is by the oxyacetylene flame. Propane and other gases are sometimes used on smaller sizes. A slightly reducing flame should be used, with a slight feather on the inner blue cone; the outer portion of the flame, pale green. Heat the tube first, beginning at about one inch from the edge of the fitting. Sweep the flames around the tube in short strokes up and down at right angles to the run of the tube. It is very important that the flame be in continuous motion and should not be allowed to remain on any one point to avoid burning through the tube. Generally, the flux may be used as a guide as to how long to heat the tube, continuing heating after the flux starts to bubble or work, and until the flux becomes quiet and transparent, like clear water. The flux will pass through four stages:


- A. At 212°F (100°C) the water boils off.
- B. At 600°F (315.6°C) the flux becomes white and slightly puffy and starts to work.
- C. At 800°F (426.7°C) it lays against the surface and has a milky appearance.
- D. At 1100°F (593.3°C) it is completely clear and active and has the appearance of water.

8. Now switch the flame to the fitting at the base of the cup. Heat uniformly, sweeping the flame from the fitting to the tube until the flux on the fitting becomes quiet. Avoid excessive heating of cast fittings.




9. When the flux appears liquid and transparent on both the tube and the fitting, start sweeping the flame back and forth along the axis of the joint to maintain heat on the parts to be joined, especially toward the base of the cup of the fitting. The flame must be kept moving to avoid burning the tube or the fitting.


10. Apply the brazing wire or rod at a point where the tube enters the socket of the fitting. The temperature of the joint should be hot enough to melt the brazing alloy. Keep the flame away from the rod or wire as it is fed into the joint. Keep both the fitting and the tube heated by moving the flame back and forth from one to the other as the alloy is drawn into the joint. When the proper temperature is reached, the alloy will flow readily into the space between the tube outer wall and the fitting socket, drawn in by the natural force of capillary attraction. When the joint is filled, a continuous fillet of brazing alloy will be visible completely around the joint. Stop feeding as soon as the joint is filled.



NOTE: For tubing one inch and larger, it is difficult to bring the whole joint up to heat at one time. It frequently will be found desirable to use a double-tip torch to maintain the proper temperature over the larger area. A mild pre-heating of the whole fitting is recommended. The heating then can proceed as in steps 7, 8, 9, and 10. If difficulty is encountered in getting the whole joint up to heat at one time, then when the joint is nearly up to the desired temperature the alloy is concentrated in a limited area. At the brazing temperature the alloy is fed into the joint and the torch is then moved to an adjacent area and the operation carried on progressively all around the joint.



**HORIZONTAL JOINTS** — When making horizontal joints, it is preferable to start applying the brazing alloy at the 5 o'clock position, then move around to the 7 o'clock position and then move up the sides to the top of the joint, making sure that the operations overlap.



**VERTICAL JOINTS** — On vertical joints, it is immaterial where the start is made. If the opening of the cup is pointed down, care should be taken to avoid overheating the tube, as this may cause the alloy to run down the tube. If this condition is encountered, take the heat away and allow the alloy to set. Then reheat the solder cup of the fitting to draw up the alloy.

After the brazing alloy has set, remove residual flux from the joint area as it is corrosive and presents an unclean appearance and condition. Hot water or steam and a soft cloth should be used. Wrot fittings may be chilled; however it is advisable to allow cast fittings to cool naturally to some extent before applying a swab. All flux must be removed before inspection and pressure testing.



**TROUBLE SPOTS**

If the alloy fails to flow or has a tendency to ball up, it indicates oxidation on the metal surfaces, or insufficient heat on the parts to be joined. If work starts to oxidize during heating, it indicates too little flux, or a flux of too thin consistency. If the brazing alloy refuses to enter the joint and tends to flow over the outside of either member of the joint, it indicates this member is overheated, or the other is underheated, or both. In both cases, operations should be stopped and the joints disassembled, re-cleaned and fluxed.




# Polybutylene Tubing


## FITTING SYSTEM – INSERT/CRIMP TYPE MADE BY NIBCO

### Making a Connection


1. Using a tube cutter, cut tubing squarely and remove burrs.




2. Slide copper crimp ring on tubing. Only copper crimp rings should be used to ensure the highest quality connection.



3. Insert fitting into tubing, then position crimp ring squarely over barbs. Proper alignment is important for making the best connection.



4. Center the crimping tool jaws exactly over the ring, and bring the tool handles together until totally closed to the stop indicator. Check each crimp ring with the caliper gauge after completion. If the small flats on the gauge do not fit over the crimped ring, the ring is undercrimped. Cut out any undercrimped rings and fittings, and completely replace.



#### TOOLS AND RINGS

- Use tools recommended by fitting and tubing manufacturers. All tools must make a full-circle crimp.
- Check tool adjustment at least daily, and readjust as necessary.
- Use crimp rings of copper as recommended by NIBCO INC.



# Frequently Asked Questions

Q: What is the pressure rating of a given fitting?

A: Fittings are rated per Table 1 of ASME B16.22. The system rated pressure shall be the lowest of the fitting, tube or joint.

Q: When copper fails in a system, what is the problem?

A: MOST COMMON:

1. Velocity – fluid is moving too fast. Recommendation: 2-3 fps (0.0508-0.0762 m/s) hot water 140°F, 5-8 fps (0.127-0.2032 m/s) cold water.
2. Turbulence – burrs left on the cut tubing causes a tumbling effect causing localized erosion and eventual failure.
3. Aggressive Waters – tend to cause pitting or green staining of fixtures. Aggressive, hard well waters that cause pitting typically are found to have total dissolved solids including sulfates and chlorides, a pH in the range of 7.2 to 7.8, a high content of carbon dioxide gas and the presence of dissolved oxygen gas. Soft acidic waters that cause green staining typically tend to be more corrosive. Low alkalinity, low mineralization, pH levels of 7 or lower should be avoided.

LESS COMMON:

1. Flux Corrosion – using too much flux when making joints can potentially leave residue and cause isolated corrosion. Flux should be used sparingly and system adequately flushed.
2. Electrolysis – stray (D.C.) current; inadequate grounding for the piping.
3. Sand or other solid particulates – erosion/corrosion problems can occur. Lower velocities must be maintained if solids are present in flow media.
4. Galvanic Corrosion – destruction of a material by electrochemical interaction between the environment and the material.

Q: Copper tubing wall thickness is designated “K,” “L” or “M.” What are the copper fittings applicable to?

A: Copper fittings’ wall thickness is determined by standards (ASME B-16:22 and MSS-SP-104). These standards address minimum wall thickness (per size) for the full range of copper fittings and are not intended to match tubing wall thicknesses.

Q: Can dissimilar metals (i.e., copper and iron) be joined together without use of dielectric insulators to prevent corrosion?

A: In most situations dissimilar metals (copper/iron/steel) can be joined successfully without using dielectric insulators. Factors to consider:

1. The composition of the two metals.
2. The rate of liquid flow past the two metals.
3. Chemicals in the water which could enhance or destroy protective films.
4. The relative areas of the two metals - unless the surface area of the less noble (steel) material is less than 5% of the more noble (copper) material, the need for a dielectric separator is not needed. (Failures due to galvanic corrosion are very unusual and only occur under very strict conditions.)
5. Local code requirements.

Q: What should the installer of copper unions know and do in order to assure a proper leak-free installation?

A. The following should be done:

1. Make sure the ground-joint (mating area of union’s tail and thread pieces) are free of nicks and scratches.
2. Spray the ground-joint area with a food grade silicone spray or apply bees wax to enhance seating.
3. Make sure alignment of line does not put lateral stress on the ground-joint seal.
4. Make sure that excess solder (droplets) do not reach the ground-joint area.



# Residential Copper Plumbing Products Limited Warranty

## What the warranty terms mean

In this warranty, the term, "Manufacturer", refers to NIBCO® which manufactured the Product and any person or company that assumes its obligations under this warranty. The term, "Owner", means you as the owner of the building in the United States in which the Product has been installed and also means any succeeding owner during the original warranty term. The term, "Product", means the copper or brass fittings manufactured by the Manufacturer for the building market in the United States.

## Date the warranty begins

If the Product was installed at the time the home was manufactured, then the warranty begins on the date the new home was first purchased. In the case of home additions or renovations, or in the case of a commercial installation, the warranty begins on the date the installation of the Product is completed. The warranty is transferable to succeeding Owners for the remainder of the original warranty term, in which case the date the warranty begins shall continue without change.

## What is covered

The Manufacturer warrants to the Owner, for a period of 50 years from the date the warranty begins, that its properly installed Product will be free of failure as a result of defects in material or workmanship in manufacturing the Product.

## What the manufacturer will do for you

As long as (1) such failure occurs within 50 years from the date the warranty begins and (2) the Owner promptly notifies the Manufacturer of the Product of that failure by contacting it through its Technical Services phone number listed below, the Manufacturer will correct that failure by repairing or replacing the Product within a reasonable time, without charge. This warranty is limited to the cost of repairing or replacing the Product, including installation.

**NIBCO TECHNICAL SERVICE**  
1-888-446-4226

## What is not covered: Disclaimer of liability for consequential and other damages

The Manufacturer does NOT warrant against failure:

1. of any product, parts, or systems that it has not manufactured;
2. if the product is used for purposes other than plumbing applications
3. caused by, contributed in whole or in part by, or resulting from, any of the following:
  - (a) improper installation;
  - (b) abuse, such as, without limitation, vandalism;
  - (c) natural disasters, such as, without limitation, flooding, windstorm or lightning;
  - (d) external causes, where external, physical or chemical qualities produce damage to the Product, such as, without limitation, aggressive water or an unsuitable or hostile environment or (e) external causes, where external, physical or chemical qualities produce damage to the Product, such as, without limitation, aggressive water or an unsuitable or hostile environment; or
  - (e) attachments or modifications to the Product that the Manufacturer did not authorize; or
  - (f) any other cause beyond the Manufacturer's control.

The Manufacturer shall NOT be liable under any circumstances for any other direct or indirect, incidental or consequential damages of any kind.

## This is the only warranty

This warranty is the only warranty for the Product provided by the Manufacturer, and is and shall be in lieu of any and all other warranties, express or implied, including, but not limited to an implied warranty of merchantability, and of all other obligations or liabilities on the part of the Manufacturer. None of the Manufacturer's employees, and no other person or business, is authorized to make any other warranty on the Manufacturer's behalf covering the product.

This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.


# Numerical Index

Figure Number	Page	Figure Number	Page	Figure Number	Page	Figure Number	Page
100 Series				735.....	11	837.....	36
Cast Heavy Flared				736.....	11	851.....	34
101.....	23			739.....	16	851-C.....	34
104.....	23			741.....	15	861-LH.....	36
				748.....	21	875-S.....	40
				749.....	21	878.....	40
				750.....	8	879.....	40
500 Series Cast Flared		700 Series		750-3.....	8	880.....	39
500.....	24	Cast Pressure		750-4.....	8	881.....	39
503.....	23	701.....	10	764.....	15	884.....	39
504.....	23	701-D.....	10	771.....	16	885.....	39
507.....	23	702.....	10	775.....	16	890.....	39
507-3.....	23	703.....	6			891.....	39
507-4.....	23	703-2.....	6			892.....	39
511.....	24	703-5.....	6			892-3.....	39
		703-5B.....	6			892-A.....	39
		704.....	7	800 Series Cast DWV			
		704-2.....	7	801.....	34		
		704-2-H.....	8	801-2.....	33		
		704-F.....	7	801-2-7.....	31		
		704-H.....	7	801-T.....	32	900 Series Wrot DWV	
600 Series		705.....	16	802.....	32	901.....	34
Wrot Pressure		705-D.....	17	802-C.....	32	901-2.....	33
600.....	9	706-2.....	12	802-F.....	32	901-2-7.....	31
600-2.....	15	707.....	12	803.....	32	901-2-F.....	33
600-DS.....	10	707-2-4.....	13	803-2.....	32	901-7.....	31
600-RS.....	9	707-3.....	14	804.....	32	901-RP.....	34
601.....	10	707-3-5.....	14	804-2.....	33	903.....	32
603.....	6	707-3-5-A.....	14	804-T.....	33	903-2.....	32
603-2.....	6	707-3-6.....	14	805.....	31	903-7.....	31
604.....	7	707-4.....	14	805-N.....	31	904.....	33
604-2.....	7	707-4-6.....	14	806.....	35	904-7.....	31
606.....	11	707-5.....	14	806-2.....	35	905.....	31
606-2.....	11	707-5-A.....	14	807.....	35	906.....	35
607.....	12	707-6.....	15	807-2.....	35	906-2.....	35
607-2.....	13	708.....	15	807-3.....	36	907.....	35
607-2-2.....	13	710-3.....	17	807-4.....	36	907-2.....	35
607-2-2-LT.....	13	710-3-4.....	17	807-9.....	36	907-LT.....	35
607-2-I.....	13	711.....	19	808.....	36	911.....	37
607-2-LT.....	13	711-5.....	19	809.....	36	917-B.....	37
607-I.....	12	711-A.....	19	810.....	38	951.....	34
607-LT.....	12	712.....	20	811.....	37	960.....	36
611.....	17-19	712-5.....	20	811-14.....	37		
611-2.....	19	713.....	20	811-15.....	37		
616.....	16	714.....	20	812.....	38		
617.....	9	717.....	9	814.....	38		
618.....	8	717-D.....	9	816.....	33		
618-3.....	8	718-3.....	8	816-S.....	33		
619.....	8	724-5-A.....	10	818 A.S.A.....	36		
620-L.....	8	733.....	21	834.....	38		
621.....	21	733-2.....	21	835.....	37		
623.....	16	733-3.....	21	835-B.....	37		
624.....	16	733-4.....	21	836.....	38		
633-W.....	21						
638.....	16						
698.....	20						

Copper Insert Fittings for Polybutylene

PB198.....	29
PB600.....	29
PB600-FA.....	29
PB607.....	29
PB607-FA.....	29
PB611.....	29

# globally connecting you at all levels



It's a new age of business, and a new way at NIBCO. From Elkhart, Indiana to Lodz, Poland, and points beyond, our company has integrated manufacturing, distribution, and networked communications to provide a seamless source of information and service, 24 hours a day, 7 days a week. But this integration hasn't happened overnight. It's been part of a long-term strategic process that has pushed us to reconsider every aspect of our business. The result? We're a vertically integrated manufacturer with the products and systems in place to deliver low cost and high quality. NIBCO's products are manufactured under a Quality Management System conforming to the current revision of ISO-9001 International Standards. We know the flow control industry is only going to get more demanding, and we are more than ready. We will continue to lead. That's what NIBCO is all about.




# FEATURING NIBCO® SYSTEMS

C-CF-0508

NIBCO® DURA-PEX® Piping Systems • NIBCO® Press System®

## FITTINGS



Wrot and cast copper pressure and drainage fittings • Cast copper alloy flanges  
• Wrot and cast press fittings • ABS and PVC DWV fittings • Schedule 40 PVC  
pressure fittings • CPVC CTS fittings • CPVC CTS-to-metal transition fittings •  
Schedule 80 PVC and CPVC systems • CPVC metric piping systems • CPVC  
BlazeMaster® fire protection fittings

BlazeMaster® is a registered trademark of The Lubrizol Corporation.

## VALVES & ACTUATION

Pressure-rated bronze, iron and alloy-iron gate, globe and check valves • Pressure-  
rated bronze ball valves • Boiler specialty valves • Commercial and industrial  
butterfly valves • Circuit balancing valves • Carbon and stainless steel ball valves  
• ANSI flanged steel ball valves • Pneumatic and electric actuators and controls  
• Grooved ball and butterfly valves • High performance butterfly valves • UL/FM  
fire protection valves • MSS specification valves • Bronze specialty valves • Low  
pressure gate, globe, check and ball valves • Frostproof sillcocks • Quarter-turn  
supply stops • Quarter-turn low pressure valves • PVC ball valves • CPVC CTS ball  
valves • Just Right® recirculating valves



## CHEMTROL®




Thermoplastic pipe, valves and fittings in PVC, Corzan® CPVC, polypropylene  
and PVDF Kynar® • Pneumatic and electric actuation systems

Corzan® is a registered trademark of The Lubrizol Corporation. • Kynar® is a registered trademark of Arkema Inc.

## TOLCO®

Pipe attachments • Structural attachments • Pipe rollers • Threaded products  
and accessories • Seismic components • Standard and specialty supports  
• TOL-Strut® channel and components • Markets served include commercial,  
industrial & fire protection



## eNIBCO



EDI—Electronic Data Interchange • VMI—Vendor Managed Inventory •  
NIBCO.com • NIBCOpartner.com

# NIBCO®

AHEAD OF THE FLOW®

**NIBCO INC.**  
**WORLD HEADQUARTERS**  
WEB: [www.nibco.com](http://www.nibco.com)

1516 MIDDLEBURY STREET  
ELKHART, IN 46516-4740  
USA

DOMESTIC CUSTOMER SERVICE  
PHONE: 800.234.0227  
FAX: 800.234.0557

TECHNICAL SERVICE  
PHONE: 888.446.4226  
FAX: 888.336.4226

INTERNATIONAL OFFICE  
PHONE: +1/574.295.3327  
FAX: +1/574.295.3455